

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	39.86	1.01
0.05	40.07	1.01
0.1	39.98	1.01
0.2	40.01	1.01
0.3	40.01	1.01
0.4	40.04	1.01
0.5	40.06	1.01
0.6	40.06	1.01
0.7	40.07	1.01
0.8	40.08	1.01
0.9	40.09	1.02
1.0	40.08	1.02
1.4	40.11	1.03
1.8	40.13	1.05
2.0	40.14	1.07
2.4	40.16	1.08
2.8	40.16	1.09
3.0	40.17	1.09
3.4	40.18	1.08
3.8	40.18	1.08
4.0	40.18	1.07
4.4	40.16	1.06
4.8	40.14	1.06
5.0	40.11	1.08
5.4	40.08	1.08
5.8	40.03	1.08
6.0	40.03	1.07
6.4	40.01	1.06
6.8	39.99	1.07
7.0	40.00	1.08
7.4	39.98	1.11
7.8	39.97	1.14
8.0	39.97	1.14
8.4	39.98	1.14
8.8	39.96	1.15
9.0	39.96	1.15
9.4	39.94	1.15
9.8	39.89	1.16
10.0	39.87	1.16
10.4	39.79	1.16
10.8	39.73	1.13
11.0	39.70	1.11
11.4	39.67	1.08
11.8	39.63	1.07
12.0	39.62	1.07
12.4	39.56	1.10
12.8	39.55	1.12
13.0	39.52	1.14
13.4	39.51	1.15
13.8	39.49	1.16
14.0	39.46	1.17
14.4	39.43	1.19
14.8	39.40	1.19
15.0	39.36	1.19
15.4	39.32	1.16
15.8	39.32	1.14
16.0	39.33	1.13
16.4	39.33	1.11
16.8	39.34	1.11
17.0	39.30	1.13
17.4	39.28	1.18
17.8	39.22	1.24
18.0	39.23	1.26