

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	10.15	1.01
0.05	10.17	1.01
0.1	10.17	1.01
0.2	10.18	1.01
0.3	10.19	1.01
0.4	10.20	1.01
0.5	10.21	1.01
0.6	10.22	1.01
0.7	10.22	1.01
0.8	10.23	1.01
0.9	10.23	1.01
1.0	10.23	1.01
1.4	10.25	1.01
1.8	10.26	1.01
2.0	10.26	1.01
2.4	10.27	1.02
2.8	10.28	1.02
3.0	10.28	1.03
3.4	10.29	1.04
3.8	10.29	1.05
4.0	10.28	1.05
4.4	10.28	1.05
4.8	10.28	1.05
5.0	10.27	1.05
5.4	10.27	1.04
5.8	10.26	1.04
6.0	10.26	1.04
6.4	10.25	1.04
6.8	10.25	1.06
7.0	10.25	1.07
7.4	10.24	1.08
7.8	10.22	1.09
8.0	10.22	1.10
8.4	10.21	1.09
8.8	10.18	1.09
9.0	10.17	1.08
9.4	10.16	1.08
9.8	10.14	1.10
10.0	10.14	1.10
10.4	10.14	1.13
10.8	10.16	1.15
11.0	10.15	1.16
11.4	10.17	1.16
11.8	10.18	1.15
12.0	10.17	1.13
12.4	10.15	1.11
12.8	10.15	1.08
13.0	10.12	1.06
13.4	10.12	1.04
13.8	10.10	1.04
14.0	10.09	1.05
14.4	10.08	1.08
14.8	10.11	1.10
15.0	10.10	1.11
15.4	10.11	1.13
15.8	10.12	1.14
16.0	10.13	1.14
16.4	10.11	1.15
16.8	10.15	1.15
17.0	10.14	1.15
17.4	10.16	1.13
17.8	10.16	1.10
18.0	10.18	1.09