

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	30.18	1.01
0.05	30.18	1.01
0.1	30.19	1.01
0.2	30.21	1.01
0.3	30.21	1.01
0.4	30.21	1.01
0.5	30.22	1.01
0.6	30.22	1.02
0.7	30.23	1.02
0.8	30.23	1.02
0.9	30.23	1.02
1.0	30.24	1.02
1.4	30.24	1.03
1.8	30.24	1.03
2.0	30.24	1.04
2.4	30.24	1.04
2.8	30.24	1.05
3.0	30.23	1.05
3.4	30.23	1.05
3.8	30.21	1.05
4.0	30.21	1.05
4.4	30.21	1.05
4.8	30.19	1.05
5.0	30.18	1.06
5.4	30.18	1.06
5.8	30.16	1.08
6.0	30.15	1.08
6.4	30.13	1.09
6.8	30.11	1.11
7.0	30.10	1.11
7.4	30.09	1.12
7.8	30.07	1.13
8.0	30.05	1.13
8.4	30.03	1.12
8.8	29.99	1.10
9.0	29.98	1.09
9.4	29.96	1.07
9.8	29.91	1.05
10.0	29.92	1.04
10.4	29.89	1.02
10.8	29.87	1.03
11.0	29.87	1.04
11.4	29.84	1.06
11.8	29.84	1.08
12.0	29.82	1.09
12.4	29.79	1.09
12.8	29.80	1.09
13.0	29.80	1.09
13.4	29.74	1.09
13.8	29.72	1.08
14.0	29.72	1.07
14.4	29.64	1.07
14.8	29.68	1.07
15.0	29.62	1.07
15.4	29.59	1.06
15.8	29.56	1.05
16.0	29.55	1.05
16.4	29.47	1.02
16.8	29.55	1.02
17.0	29.50	1.04
17.4	29.46	1.08
17.8	29.43	1.13
18.0	29.45	1.15