

# Directional Coupler

# DBTC-9-4L+

## Typical Performance Data

TEST CONDITIONS: INPUT POWER =0 dBm @Temperature = +25°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING LOSS (dB)	DIRECTIVITY (dB)	RETURN LOSS (dB)		
				IN	OUT	CPL
5	1.06	8.81	21.08	19.70	29.29	19.54
10	1.03	8.81	21.30	20.11	31.39	19.98
20	1.04	8.82	21.32	20.27	32.33	20.14
50	1.06	8.84	21.22	20.41	32.51	20.21
100	1.08	8.86	21.03	20.62	32.07	20.28
150	1.09	8.88	20.83	20.82	31.69	20.22
200	1.10	8.89	20.55	20.98	31.23	20.08
250	1.11	8.89	20.24	21.09	30.83	19.85
300	1.12	8.90	19.88	21.23	30.39	19.52
350	1.12	8.90	19.52	21.30	29.99	19.15
400	1.14	8.90	19.11	21.42	29.41	18.75
450	1.15	8.90	18.67	21.47	28.92	18.31
500	1.16	8.90	18.26	21.55	28.42	17.82
550	1.18	8.90	17.84	21.62	27.99	17.36
600	1.19	8.89	17.41	21.68	27.45	16.91
650	1.21	8.89	16.99	21.65	26.83	16.45
700	1.23	8.89	16.56	21.61	26.30	15.98
750	1.25	8.89	16.15	21.60	25.84	15.54
800	1.27	8.89	15.75	21.53	25.28	15.15
850	1.29	8.88	15.34	21.44	24.68	14.73
900	1.32	8.88	14.96	21.27	24.16	14.30
950	1.35	8.88	14.59	21.16	23.56	13.92
1000	1.38	8.87	14.24	21.02	22.99	13.57
1050	1.41	8.87	13.89	20.85	22.48	13.21
1100	1.45	8.86	13.53	20.65	22.01	12.86
1150	1.49	8.85	13.21	20.43	21.45	12.54
1200	1.53	8.84	12.87	20.23	20.89	12.27
1250	1.57	8.83	12.55	19.98	20.37	11.98
1300	1.61	8.81	12.21	19.72	19.90	11.70
1400	1.72	8.78	11.59	19.14	18.84	11.25
1500	1.83	8.73	11.01	18.61	17.89	10.81
1600	1.96	8.67	10.47	18.14	16.98	10.51
1700	2.10	8.59	9.94	17.67	16.14	10.19
1800	2.25	8.50	9.41	17.28	15.35	9.99
1900	2.43	8.40	8.94	16.82	14.59	9.78
2000	2.62	8.28	8.50	16.48	13.86	9.66
2100	2.83	8.16	8.10	16.17	13.20	9.54
2200	3.06	8.03	7.76	16.06	12.57	9.51
2300	3.31	7.90	7.43	15.98	12.01	9.43
2400	3.59	7.77	7.16	15.89	11.43	9.45
2500	3.88	7.64	6.92	15.97	10.97	9.44
2600	4.19	7.54	6.71	16.06	10.49	9.46
2700	4.55	7.42	6.55	16.35	10.11	9.51
2800	4.92	7.34	6.40	16.66	9.71	9.57
2900	5.31	7.26	6.28	17.17	9.39	9.66
3000	5.76	7.22	6.14	17.66	9.06	9.80
3250	7.07	7.26	5.66	19.36	8.39	10.51
3500	8.74	7.59	4.77	18.77	7.90	12.06
3750	10.88	8.28	3.54	15.17	7.56	15.20
4000	13.47	9.29	2.44	12.02	7.32	20.51
4500	19.42	11.85	1.49	8.77	6.58	14.00
4750	20.88	13.04	1.09	7.83	5.90	11.11
5000	20.33	13.85	0.99	7.11	5.26	9.32

REV. X1  
DBTC-9-4L+  
081110  
Page 1 of 3



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS 9100 CERTIFIED RoHS compliant  
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



# Directional Coupler

# DBTC-9-4L+

## Typical Performance Data

TEST CONDITIONS: INPUT POWER =0 dBm @Temperature = -40°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING LOSS (dB)	DIRECTIVITY (dB)	RETURN LOSS (dB)		
				IN	OUT	CPL
5	1.20	8.88	20.22	17.94	24.49	17.65
10	1.06	8.77	20.60	19.50	27.80	19.24
20	1.00	8.73	20.93	20.47	30.01	20.25
50	0.97	8.74	21.34	21.08	29.67	20.77
100	0.98	8.75	20.97	21.30	28.92	21.07
150	0.98	8.75	20.89	21.49	29.24	21.00
200	0.99	8.76	20.68	21.67	28.89	20.79
250	0.99	8.76	20.21	21.58	28.67	20.42
300	1.00	8.76	19.99	21.72	28.48	19.90
350	1.01	8.76	19.55	21.64	28.31	19.41
400	1.01	8.76	19.18	21.71	28.06	18.92
450	1.02	8.75	18.77	21.86	28.11	18.43
500	1.03	8.75	18.31	21.78	27.64	17.93
550	1.04	8.75	17.89	21.77	27.37	17.46
600	1.06	8.74	17.49	21.77	26.98	16.99
650	1.07	8.73	17.02	21.55	26.35	16.51
700	1.08	8.72	16.63	21.49	26.05	16.04
750	1.10	8.71	16.25	21.59	25.90	15.64
800	1.11	8.70	15.77	21.34	25.31	15.28
850	1.12	8.69	15.41	21.17	24.63	14.89
900	1.15	8.68	15.01	21.10	24.47	14.49
950	1.17	8.67	14.59	20.91	23.89	14.12
1000	1.20	8.66	14.25	20.90	23.52	13.78
1050	1.23	8.65	13.88	20.69	23.00	13.47
1100	1.26	8.63	13.54	20.54	22.61	13.16
1150	1.29	8.61	13.24	20.68	22.38	12.87
1200	1.32	8.58	12.86	20.39	21.45	12.64
1250	1.36	8.57	12.48	19.78	20.67	12.40
1300	1.39	8.54	12.18	19.58	20.29	12.16
1400	1.48	8.49	11.59	19.20	19.25	11.78
1500	1.57	8.43	10.88	18.64	18.39	11.42
1600	1.68	8.35	10.57	18.47	17.43	11.20
1700	1.79	8.27	10.02	18.23	16.79	10.97
1800	1.95	8.17	9.37	17.44	15.59	10.83
1900	2.09	8.04	8.99	17.49	15.02	10.72
2000	2.26	7.95	8.60	16.86	14.15	10.58
2100	2.44	7.81	8.18	16.99	13.66	10.49
2200	2.66	7.69	7.76	16.63	12.88	10.44
2300	2.88	7.56	7.50	16.99	12.28	10.26
2400	3.14	7.45	7.18	16.49	11.62	10.13
2500	3.39	7.35	6.93	16.83	11.36	9.98
2600	3.71	7.28	6.76	15.79	10.46	9.63
2700	4.01	7.18	6.59	16.81	10.23	9.42
2800	4.35	7.15	6.54	17.06	9.79	9.09
2900	4.70	7.09	6.42	17.22	9.44	8.84
3000	5.14	7.08	6.34	17.55	8.95	8.62
3250	6.38	7.20	5.89	18.82	8.21	8.38
3500	8.02	7.58	4.98	18.09	7.75	8.85
3750	10.20	8.24	3.65	15.34	7.27	10.84
4000	12.88	9.20	2.54	12.01	7.19	15.37
4500	18.99	11.80	1.93	8.74	6.51	18.28
4750	20.94	13.15	1.28	7.85	5.82	12.39
5000	20.67	14.07	0.76	7.30	5.20	9.70

REV. X1  
DBTC-9-4L+  
081110  
Page 2 of 3



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS 9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



# Directional Coupler

# DBTC-9-4L+

## Typical Performance Data

TEST CONDITIONS: INPUT POWER =0 dBm @Temperature = +85°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING LOSS (dB)	DIRECTIVITY (dB)	RETURN LOSS (dB)		
				IN	OUT	CPL
5	1.20	8.91	21.22	18.81	32.67	18.89
10	1.20	8.91	21.22	19.05	36.81	19.11
20	1.21	8.92	21.08	19.13	39.43	19.19
50	1.24	8.95	20.76	19.22	41.25	19.27
100	1.25	8.98	20.74	19.47	41.84	19.36
150	1.26	8.99	20.50	19.77	38.53	19.40
200	1.27	9.01	20.08	19.99	38.06	19.41
250	1.27	9.01	19.86	20.24	36.81	19.31
300	1.28	9.02	19.40	20.40	35.77	19.13
350	1.29	9.03	19.05	20.56	34.94	18.89
400	1.30	9.04	18.64	20.78	33.61	18.62
450	1.31	9.04	18.17	20.90	32.48	18.29
500	1.33	9.05	17.75	21.07	31.34	17.89
550	1.35	9.07	17.34	21.24	30.59	17.51
600	1.37	9.07	16.93	21.41	29.75	17.10
650	1.38	9.08	16.54	21.51	28.73	16.66
700	1.40	9.09	16.14	21.62	27.98	16.20
750	1.43	9.10	15.73	21.64	27.26	15.77
800	1.45	9.11	15.37	21.65	26.40	15.37
850	1.47	9.11	15.04	21.73	25.66	14.95
900	1.50	9.12	14.68	21.62	25.02	14.52
950	1.54	9.13	14.31	21.57	24.30	14.12
1000	1.58	9.13	13.98	21.53	23.66	13.76
1050	1.62	9.14	13.64	21.34	23.06	13.42
1100	1.66	9.13	13.31	21.22	22.57	13.07
1150	1.71	9.13	12.97	20.99	21.86	12.74
1200	1.75	9.11	12.65	20.76	21.23	12.46
1250	1.80	9.10	12.36	20.61	20.72	12.18
1300	1.84	9.08	12.02	20.43	20.33	11.93
1400	1.95	9.05	11.38	19.84	19.17	11.48
1500	2.08	9.00	10.81	19.42	18.25	11.05
1600	2.22	8.94	10.22	19.02	17.38	10.79
1700	2.36	8.87	9.72	18.43	16.39	10.48
1800	2.52	8.79	9.20	18.24	15.79	10.30
1900	2.70	8.70	8.69	17.93	15.21	10.13
2000	2.89	8.60	8.28	17.56	14.34	9.99
2100	3.10	8.51	7.87	17.13	13.65	9.87
2200	3.32	8.40	7.59	17.01	13.09	9.84
2300	3.56	8.30	7.23	17.12	12.60	9.71
2400	3.81	8.20	6.99	16.94	11.99	9.73
2500	4.08	8.10	6.80	16.86	11.53	9.65
2600	4.35	8.02	6.61	17.42	11.13	9.63
2700	4.66	7.92	6.49	17.30	10.75	9.61
2800	4.97	7.82	6.34	17.74	10.39	9.60
2900	5.30	7.72	6.31	17.87	10.01	9.58
3000	5.66	7.65	6.28	18.22	9.68	9.63
3250	6.73	7.54	6.02	19.31	8.94	9.88
3500	8.07	7.58	5.41	19.37	8.29	10.65
3750	9.78	7.88	4.29	16.14	7.86	12.43
4000	11.92	8.47	2.94	12.59	7.50	15.69
4500	17.17	10.39	1.64	8.30	7.11	15.19
4750	19.30	11.44	1.36	7.26	6.42	11.67
5000	19.52	12.41	1.34	6.45	5.68	9.44

REV. X1  
DBTC-9-4L+  
081110  
Page 3 of 3



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS 9100 CERTIFIED RoHS compliant  
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see

