

Directional Coupler

DBTC-9-4LX+

Typical Performance Data

TEST CONDITIONS: INPUT POWER =0 dBm @Temperature = +25°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING LOSS (dB)	DIRECTIVITY (dB)	RETURN LOSS		
				IN	OUT	CPL
5	1.06	8.81	21.08	19.70	29.29	19.54
10	1.03	8.81	21.30	20.11	31.39	19.98
20	1.04	8.82	21.32	20.27	32.33	20.14
50	1.06	8.84	21.22	20.41	32.51	20.21
100	1.08	8.86	21.03	20.62	32.07	20.28
150	1.09	8.88	20.83	20.82	31.69	20.22
200	1.10	8.89	20.55	20.98	31.23	20.08
250	1.11	8.89	20.24	21.09	30.83	19.85
300	1.12	8.90	19.88	21.23	30.39	19.52
350	1.12	8.90	19.52	21.30	29.99	19.15
400	1.14	8.90	19.11	21.42	29.41	18.75
450	1.15	8.90	18.67	21.47	28.92	18.31
500	1.16	8.90	18.26	21.55	28.42	17.82
550	1.18	8.90	17.84	21.62	27.99	17.36
600	1.19	8.89	17.41	21.68	27.45	16.91
650	1.21	8.89	16.99	21.65	26.83	16.45
700	1.23	8.89	16.56	21.61	26.30	15.98
750	1.25	8.89	16.15	21.60	25.84	15.54
800	1.27	8.89	15.75	21.53	25.28	15.15
850	1.29	8.88	15.34	21.44	24.68	14.73
900	1.32	8.88	14.96	21.27	24.16	14.30
950	1.35	8.88	14.59	21.16	23.56	13.92
1000	1.38	8.87	14.24	21.02	22.99	13.57
1050	1.41	8.87	13.89	20.85	22.48	13.21
1100	1.45	8.86	13.53	20.65	22.01	12.86
1150	1.49	8.85	13.21	20.43	21.45	12.54
1200	1.53	8.84	12.87	20.23	20.89	12.27
1250	1.57	8.83	12.55	19.98	20.37	11.98
1300	1.61	8.81	12.21	19.72	19.90	11.70
1400	1.72	8.78	11.59	19.14	18.84	11.25
1500	1.83	8.73	11.01	18.61	17.89	10.81
1600	1.96	8.67	10.47	18.14	16.98	10.51
1700	2.10	8.59	9.94	17.67	16.14	10.19
1800	2.25	8.50	9.41	17.28	15.35	9.99
1900	2.43	8.40	8.94	16.82	14.59	9.78
2000	2.62	8.28	8.50	16.48	13.86	9.66
2100	2.83	8.16	8.10	16.17	13.20	9.54
2200	3.06	8.03	7.76	16.06	12.57	9.51
2300	3.31	7.90	7.43	15.98	12.01	9.43
2400	3.59	7.77	7.16	15.89	11.43	9.45
2500	3.88	7.64	6.92	15.97	10.97	9.44
2600	4.19	7.54	6.71	16.06	10.49	9.46
2700	4.55	7.42	6.55	16.35	10.11	9.51
2800	4.92	7.34	6.40	16.66	9.71	9.57
2900	5.31	7.26	6.28	17.17	9.39	9.66
3000	5.76	7.22	6.14	17.66	9.06	9.80
3250	7.07	7.26	5.66	19.36	8.39	10.51
3500	8.74	7.59	4.77	18.77	7.90	12.06
3750	10.88	8.28	3.54	15.17	7.56	15.20
4000	13.47	9.29	2.44	12.02	7.32	20.51
4500	19.42	11.85	1.49	8.77	6.58	14.00
4750	20.88	13.04	1.09	7.83	5.90	11.11
5000	20.33	13.85	0.99	7.11	5.26	9.32



REV. X1
DBTC-9-4LX+
3/8/2012
Page 1 of 3

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

Directional Coupler

DBTC-9-4LX+

Typical Performance Data

TEST CONDITIONS: INPUT POWER =0 dBm @Temperature = -40°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING LOSS (dB)	DIRECTIVITY (dB)	RETURN LOSS		
				IN	(dB) OUT	CPL
5	1.20	8.88	20.22	17.94	24.49	17.65
10	1.06	8.77	20.60	19.50	27.80	19.24
20	1.00	8.73	20.93	20.47	30.01	20.25
50	0.97	8.74	21.34	21.08	29.67	20.77
100	0.98	8.75	20.97	21.30	28.92	21.07
150	0.98	8.75	20.89	21.49	29.24	21.00
200	0.99	8.76	20.68	21.67	28.89	20.79
250	0.99	8.76	20.21	21.58	28.67	20.42
300	1.00	8.76	19.99	21.72	28.48	19.90
350	1.01	8.76	19.55	21.64	28.31	19.41
400	1.01	8.76	19.18	21.71	28.06	18.92
450	1.02	8.75	18.77	21.86	28.11	18.43
500	1.03	8.75	18.31	21.78	27.64	17.93
550	1.04	8.75	17.89	21.77	27.37	17.46
600	1.06	8.74	17.49	21.77	26.98	16.99
650	1.07	8.73	17.02	21.55	26.35	16.51
700	1.08	8.72	16.63	21.49	26.05	16.04
750	1.10	8.71	16.25	21.59	25.90	15.64
800	1.11	8.70	15.77	21.34	25.31	15.28
850	1.12	8.69	15.41	21.17	24.63	14.89
900	1.15	8.68	15.01	21.10	24.47	14.49
950	1.17	8.67	14.59	20.91	23.89	14.12
1000	1.20	8.66	14.25	20.90	23.52	13.78
1050	1.23	8.65	13.88	20.69	23.00	13.47
1100	1.26	8.63	13.54	20.54	22.61	13.16
1150	1.29	8.61	13.24	20.68	22.38	12.87
1200	1.32	8.58	12.86	20.39	21.45	12.64
1250	1.36	8.57	12.48	19.78	20.67	12.40
1300	1.39	8.54	12.18	19.58	20.29	12.16
1400	1.48	8.49	11.59	19.20	19.25	11.78
1500	1.57	8.43	10.88	18.64	18.39	11.42
1600	1.68	8.35	10.57	18.47	17.43	11.20
1700	1.79	8.27	10.02	18.23	16.79	10.97
1800	1.95	8.17	9.37	17.44	15.59	10.83
1900	2.09	8.04	8.99	17.49	15.02	10.72
2000	2.26	7.95	8.60	16.86	14.15	10.58
2100	2.44	7.81	8.18	16.99	13.66	10.49
2200	2.66	7.69	7.76	16.63	12.88	10.44
2300	2.88	7.56	7.50	16.99	12.28	10.26
2400	3.14	7.45	7.18	16.49	11.62	10.13
2500	3.39	7.35	6.93	16.83	11.36	9.98
2600	3.71	7.28	6.76	15.79	10.46	9.63
2700	4.01	7.18	6.59	16.81	10.23	9.42
2800	4.35	7.15	6.54	17.06	9.79	9.09
2900	4.70	7.09	6.42	17.22	9.44	8.84
3000	5.14	7.08	6.34	17.55	8.95	8.62
3250	6.38	7.20	5.89	18.82	8.21	8.38
3500	8.02	7.58	4.98	18.09	7.75	8.85
3750	10.20	8.24	3.65	15.34	7.27	10.84
4000	12.88	9.20	2.54	12.01	7.19	15.37
4500	18.99	11.80	1.93	8.74	6.51	18.28
4750	20.94	13.15	1.28	7.85	5.82	12.39
5000	20.67	14.07	0.76	7.30	5.20	9.70



REV. X1
DBTC-9-4LX+
3/8/2012
Page 2 of 3

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

Directional Coupler

DBTC-9-4LX+

Typical Performance Data

TEST CONDITIONS: INPUT POWER =0 dBm @Temperature = +85°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING LOSS (dB)	DIRECTIVITY (dB)	RETURN LOSS		
				IN	(dB) OUT	CPL
5	1.20	8.91	21.22	18.81	32.67	18.89
10	1.20	8.91	21.22	19.05	36.81	19.11
20	1.21	8.92	21.08	19.13	39.43	19.19
50	1.24	8.95	20.76	19.22	41.25	19.27
100	1.25	8.98	20.74	19.47	41.84	19.36
150	1.26	8.99	20.50	19.77	38.53	19.40
200	1.27	9.01	20.08	19.99	38.06	19.41
250	1.27	9.01	19.86	20.24	36.81	19.31
300	1.28	9.02	19.40	20.40	35.77	19.13
350	1.29	9.03	19.05	20.56	34.94	18.89
400	1.30	9.04	18.64	20.78	33.61	18.62
450	1.31	9.04	18.17	20.90	32.48	18.29
500	1.33	9.05	17.75	21.07	31.34	17.89
550	1.35	9.07	17.34	21.24	30.59	17.51
600	1.37	9.07	16.93	21.41	29.75	17.10
650	1.38	9.08	16.54	21.51	28.73	16.66
700	1.40	9.09	16.14	21.62	27.98	16.20
750	1.43	9.10	15.73	21.64	27.26	15.77
800	1.45	9.11	15.37	21.65	26.40	15.37
850	1.47	9.11	15.04	21.73	25.66	14.95
900	1.50	9.12	14.68	21.62	25.02	14.52
950	1.54	9.13	14.31	21.57	24.30	14.12
1000	1.58	9.13	13.98	21.53	23.66	13.76
1050	1.62	9.14	13.64	21.34	23.06	13.42
1100	1.66	9.13	13.31	21.22	22.57	13.07
1150	1.71	9.13	12.97	20.99	21.86	12.74
1200	1.75	9.11	12.65	20.76	21.23	12.46
1250	1.80	9.10	12.36	20.61	20.72	12.18
1300	1.84	9.08	12.02	20.43	20.33	11.93
1400	1.95	9.05	11.38	19.84	19.17	11.48
1500	2.08	9.00	10.81	19.42	18.25	11.05
1600	2.22	8.94	10.22	19.02	17.38	10.79
1700	2.36	8.87	9.72	18.43	16.39	10.48
1800	2.52	8.79	9.20	18.24	15.79	10.30
1900	2.70	8.70	8.69	17.93	15.21	10.13
2000	2.89	8.60	8.28	17.56	14.34	9.99
2100	3.10	8.51	7.87	17.13	13.65	9.87
2200	3.32	8.40	7.59	17.01	13.09	9.84
2300	3.56	8.30	7.23	17.12	12.60	9.71
2400	3.81	8.20	6.99	16.94	11.99	9.73
2500	4.08	8.10	6.80	16.86	11.53	9.65
2600	4.35	8.02	6.61	17.42	11.13	9.63
2700	4.66	7.92	6.49	17.30	10.75	9.61
2800	4.97	7.82	6.34	17.74	10.39	9.60
2900	5.30	7.72	6.31	17.87	10.01	9.58
3000	5.66	7.65	6.28	18.22	9.68	9.63
3250	6.73	7.54	6.02	19.31	8.94	9.88
3500	8.07	7.58	5.41	19.37	8.29	10.65
3750	9.78	7.88	4.29	16.14	7.86	12.43
4000	11.92	8.47	2.94	12.59	7.50	15.69
4500	17.17	10.39	1.64	8.30	7.11	15.19
4750	19.30	11.44	1.36	7.26	6.42	11.67
5000	19.52	12.41	1.34	6.45	5.68	9.44



REV. X1
DBTC-9-4LX+
3/8/2012
Page 3 of 3

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS