

Directional Coupler

EDC10-183+

Typical Performance Data

TEST CONDITIONS: INPUT POWER = 0 dBm @Temperature = +25°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING (dB)	DIRECTIVITY (dB)	RETURN LOSS		
				IN	(dB) OUT	CPL
1000	0.25	24.50	33.54	31.29	24.30	33.87
3000	0.61	15.80	19.55	14.03	18.73	13.82
6000	0.77	11.30	18.77	22.56	23.44	22.04
6500	0.81	10.94	20.42	25.32	27.54	24.57
7000	0.84	10.63	20.71	38.48	28.82	33.30
7500	0.89	10.38	19.18	31.27	24.24	31.46
8000	0.94	10.17	17.16	29.87	20.65	37.01
8500	1.03	10.03	15.51	24.67	18.49	25.62
9000	1.15	9.99	14.50	17.34	17.31	16.71
9500	1.33	10.07	13.91	13.19	16.68	12.45
10000	1.47	10.17	13.76	11.26	16.10	10.46
10500	1.50	10.19	14.10	10.94	15.37	10.11
11000	1.42	10.13	14.77	12.16	14.86	11.41
11500	1.28	9.98	15.97	15.41	15.10	15.01
12000	1.16	9.85	17.98	22.28	16.68	24.01
12500	1.14	9.81	20.01	28.84	20.26	31.98
13000	1.16	9.87	19.59	30.57	23.03	22.86
13500	1.22	10.06	16.86	19.28	18.26	16.57
14000	1.38	10.40	14.25	13.32	14.62	12.14
14500	1.47	10.63	12.59	11.74	12.37	10.91
15000	1.37	10.56	12.04	14.68	11.41	13.89
15500	1.30	10.40	12.42	22.21	11.71	19.55
16000	1.48	10.50	13.95	13.27	13.90	11.90
16500	1.66	10.72	16.69	10.45	18.02	9.23
17000	1.52	10.88	21.84	11.72	19.78	10.52
17500	1.25	10.95	22.48	19.25	17.52	17.24
18000	1.19	11.11	16.56	21.51	17.14	19.95
18500	1.28	11.14	13.04	15.91	19.26	14.68
19000	1.29	10.95	11.27	19.97	26.00	16.50
19500	1.36	10.90	10.67	21.57	28.21	15.77
20000	1.63	11.27	10.87	11.95	18.70	10.20



ISO 9001 ISO 14001 AS 9100 CERTIFIED



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS

REV. OR
EDC10-183+
10/31/2018
Page 1 of 3

Directional Coupler

EDC10-183+

Typical Performance Data

TEST CONDITIONS: INPUT POWER =0 dBm @Temperature = -40°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING (dB)	DIRECTIVITY (dB)	RETURN LOSS		
				IN	(dB) OUT	CPL
1000	0.19	24.49	34.44	32.29	24.28	34.63
3000	0.50	15.74	19.49	13.86	18.85	13.72
6000	0.60	11.16	18.86	22.22	22.65	21.80
6500	0.62	10.79	20.95	25.25	26.36	24.41
7000	0.64	10.47	21.18	37.39	27.60	35.14
7500	0.68	10.20	19.35	32.13	23.88	35.57
8000	0.72	9.99	17.53	29.95	20.74	48.73
8500	0.80	9.84	16.13	24.20	18.62	25.38
9000	0.90	9.77	15.08	18.11	17.30	17.75
9500	1.06	9.81	14.22	13.64	16.53	12.98
10000	1.24	9.93	13.73	11.00	15.91	10.18
10500	1.31	9.99	13.88	10.17	15.12	9.34
11000	1.21	9.91	14.54	11.21	14.46	10.47
11500	1.03	9.73	15.84	14.36	14.55	13.95
12000	0.90	9.59	17.82	20.51	15.88	21.92
12500	0.85	9.53	19.92	26.40	19.31	32.42
13000	0.86	9.56	20.16	29.31	23.23	23.13
13500	0.90	9.73	17.58	19.98	18.45	17.03
14000	1.06	10.07	14.53	13.08	14.44	11.99
14500	1.20	10.36	12.44	10.79	12.03	10.11
15000	1.09	10.30	11.70	13.05	10.71	12.49
15500	0.96	10.09	12.03	21.30	11.06	20.21
16000	1.11	10.14	13.48	13.48	13.21	12.33
16500	1.26	10.33	16.19	10.49	17.66	9.40
17000	1.11	10.47	20.68	11.62	21.35	10.63
17500	0.87	10.54	22.96	17.65	18.70	16.70
18000	0.78	10.68	17.56	23.18	17.27	24.80
18500	0.85	10.75	13.40	15.94	18.14	15.47
19000	0.88	10.61	10.99	17.16	22.02	16.10
19500	0.93	10.46	10.07	22.57	27.37	17.60
20000	1.21	10.79	10.36	11.76	19.46	10.24



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS

REV. OR
EDC10-183+
10/31/2018
Page 2 of 3

Directional Coupler

EDC10-183+

Typical Performance Data

TEST CONDITIONS: INPUT POWER = 0 dBm @Temperature = +85°C

FREQUENCY (MHz)	INSERTION LOSS (dB)	COUPLING (dB)	DIRECTIVITY (dB)	RETURN LOSS		
				IN	(dB) OUT	CPL
1000	0.29	24.49	32.27	30.91	24.46	33.27
3000	0.67	15.81	19.77	14.36	18.91	14.15
6000	0.88	11.38	18.64	22.21	23.92	21.73
6500	0.92	11.02	20.23	24.89	28.60	24.12
7000	0.96	10.72	20.61	36.63	30.02	32.22
7500	1.01	10.48	19.24	31.95	24.79	32.01
8000	1.07	10.28	17.16	29.90	20.91	35.47
8500	1.17	10.14	15.36	24.86	18.51	25.74
9000	1.31	10.13	14.23	17.00	17.19	16.43
9500	1.51	10.23	13.65	12.81	16.54	12.17
10000	1.64	10.33	13.60	11.18	16.02	10.45
10500	1.63	10.32	14.12	11.27	15.42	10.48
11000	1.55	10.24	14.92	12.81	15.12	12.11
11500	1.42	10.12	16.14	16.19	15.58	15.86
12000	1.33	10.01	18.01	23.05	17.17	25.14
12500	1.32	9.99	19.87	29.51	20.55	31.10
13000	1.34	10.05	19.21	31.82	22.97	22.70
13500	1.42	10.26	16.46	18.94	18.22	16.37
14000	1.58	10.61	13.91	13.15	14.62	12.07
14500	1.66	10.82	12.37	11.96	12.44	11.22
15000	1.55	10.73	12.02	15.74	11.57	15.04
15500	1.51	10.60	12.66	20.98	12.17	19.26
16000	1.70	10.73	14.41	13.06	14.73	11.84
16500	1.84	10.93	17.36	10.98	19.01	9.76
17000	1.69	11.09	22.16	12.77	19.80	11.50
17500	1.46	11.19	21.38	20.92	17.63	18.75
18000	1.43	11.34	16.16	21.16	17.49	19.98
18500	1.52	11.36	12.89	16.36	19.88	15.17
19000	1.53	11.18	11.21	20.94	27.50	17.32
19500	1.64	11.17	10.71	20.18	27.25	15.60
20000	1.91	11.57	11.14	11.84	18.09	10.24



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS

REV. OR
EDC10-183+
10/31/2018
Page 3 of 3