

# Coaxial Fixed Attenuator

# FW-15A+

## Typical Performance Data

FREQ.	ATTENUATION	VSWR
(MHz)	(dB)	(:1)
10	14.99	1.18
20	14.99	1.18
50	15.00	1.18
100	15.00	1.18
200	15.01	1.18
300	15.03	1.18
400	15.03	1.18
500	15.05	1.18
600	15.06	1.18
700	15.07	1.18
800	15.08	1.18
900	15.09	1.18
1000	15.10	1.18
1200	15.11	1.17
1400	15.13	1.17
1600	15.15	1.17
1800	15.17	1.17
2000	15.19	1.17
2200	15.20	1.17
2400	15.22	1.16
2600	15.23	1.16
2800	15.25	1.16
3000	15.27	1.15
3200	15.29	1.15
3400	15.30	1.14
3600	15.32	1.14
3800	15.34	1.14
4000	15.36	1.14
4200	15.38	1.13
4400	15.40	1.13
4600	15.42	1.14
4800	15.44	1.14
5000	15.46	1.14
5200	15.48	1.14
5400	15.50	1.14
5600	15.53	1.14
5800	15.55	1.15
6000	15.57	1.15
6200	15.59	1.15
6400	15.62	1.14
6600	15.64	1.14
6800	15.66	1.14
7000	15.69	1.13
7200	15.71	1.13
7400	15.73	1.12
7600	15.75	1.12
7800	15.77	1.11
8000	15.80	1.11
8200	15.82	1.11
8400	15.83	1.11
8600	15.86	1.11
8800	15.87	1.11
9000	15.89	1.12
9200	15.91	1.12
9400	15.93	1.13
9600	15.94	1.14
10000	15.97	1.15
11000	16.01	1.16
11500	16.01	1.15
12000	16.02	1.13



ISO 9001 ISO 14001 AS 9100 CERTIFIED



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)

IF/RF MICROWAVE COMPONENTS