

Fixed Attenuator

FW-9+

Typical Performance Data

FREQUENCY (MHz)	ATTENUATION (dB)	VSWR (:1)
10.0	9.00	1.02
50.0	9.02	1.01
100.0	9.03	1.01
500.0	9.08	1.01
1000.0	9.11	1.00
1200.0	9.13	1.00
1400.0	9.14	1.01
1600.0	9.15	1.01
1800.0	9.17	1.01
2000.0	9.18	1.02
2200.0	9.19	1.02
2400.0	9.21	1.03
2600.0	9.23	1.03
2800.0	9.24	1.03
3000.0	9.26	1.04
3200.0	9.27	1.04
3400.0	9.28	1.05
3600.0	9.30	1.05
3800.0	9.32	1.05
4000.0	9.33	1.05
4200.0	9.35	1.05
4400.0	9.36	1.06
4600.0	9.38	1.06
4800.0	9.40	1.06
5000.0	9.41	1.06
5200.0	9.44	1.07
5500.0	9.46	1.07
6000.0	9.50	1.09
6500.0	9.54	1.11
7000.0	9.60	1.14
7500.0	9.65	1.17
8000.0	9.70	1.19
8500.0	9.75	1.23
9000.0	9.77	1.26
9500.0	9.81	1.30
10000.0	9.84	1.33
10500.0	9.86	1.35
11000.0	9.89	1.35
11500.0	9.91	1.35
12000.0	9.91	1.35
12500.0	9.92	1.35
13000.0	9.88	1.32
13500.0	9.86	1.29
14000.0	9.84	1.26
14500.0	9.77	1.21
15000.0	9.78	1.15



P.O. Box 350166, Brooklyn, New York 11235-0003 • Fax (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
FW-9+
5/1/2014
Page 1 of 1