

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	7.01	1.11
0.02	7.01	1.11
0.04	7.01	1.11
0.06	7.01	1.11
0.08	7.01	1.11
0.10	7.01	1.11
0.20	7.01	1.11
0.40	7.01	1.11
0.60	7.01	1.11
0.80	7.01	1.11
1.00	7.01	1.11
1.20	7.01	1.11
1.40	7.01	1.11
1.60	7.01	1.11
1.80	7.01	1.11
2.00	7.01	1.11
3.00	7.00	1.11
4.00	7.00	1.11
5.00	7.00	1.10
6.00	6.99	1.10
7.00	7.00	1.10
8.00	6.99	1.10
9.00	7.00	1.10
10.0	6.99	1.09
11.0	7.00	1.09
12.0	7.02	1.08
13.0	7.06	1.08
14.0	7.05	1.07
15.0	7.02	1.07
16.0	7.02	1.07
17.0	7.03	1.06
18.0	7.06	1.06
19.0	7.07	1.05
20.0	7.02	1.05
21.0	7.01	1.04
22.0	7.00	1.04
23.0	7.01	1.04
24.0	6.96	1.04
25.0	6.94	1.05
26.0	6.97	1.05
27.0	6.96	1.05
28.0	6.95	1.06
29.0	6.94	1.06
30.0	6.91	1.06
31.0	6.94	1.07
32.0	6.94	1.07
33.0	6.88	1.07
34.0	6.84	1.08
35.0	6.80	1.08
36.0	6.79	1.09
37.0	6.71	1.10
38.0	6.69	1.10
39.0	6.61	1.11
40.0	6.53	1.12
41.0	6.62	1.13
42.0	6.56	1.13
43.0	6.54	1.13
43.5	6.48	1.14