

Low Pass Filter

LFCN-ED13263/2

Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	RETURN LOSS (dB)
10.0	0.07	32.12
100.0	0.16	31.80
150.0	0.19	30.90
200.0	0.21	30.20
250.0	0.23	29.84
300.0	0.25	29.51
350.0	0.28	29.47
400.0	0.30	29.21
450.0	0.32	28.79
500.0	0.34	28.32
550.0	0.36	27.26
600.0	0.39	26.74
650.0	0.42	25.98
700.0	0.45	25.29
750.0	0.48	24.48
800.0	0.52	23.79
850.0	0.57	23.05
900.0	0.62	22.28
950.0	0.69	21.30
1000.0	0.77	20.30
1050.0	0.88	19.32
1100.0	1.01	18.28
1150.0	1.19	17.34
1200.0	1.44	16.21
1225.0	1.61	15.43
1250.0	1.84	14.37
1275.0	2.15	12.89
1300.0	2.61	11.01
1305.0	2.73	10.60
1310.0	2.85	10.18
1315.0	2.99	9.77
1320.0	3.13	9.34
1325.0	3.29	8.92
1330.0	3.47	8.50
1335.0	3.66	8.08
1340.0	3.86	7.67
1345.0	4.08	7.26
1350.0	4.32	6.87
1400.0	7.82	3.71
1450.0	13.08	2.13
1500.0	18.65	1.49
1550.0	22.78	1.21
1600.0	25.17	1.06
1650.0	26.83	0.95
1700.0	28.59	0.88
1750.0	30.76	0.82
1800.0	33.59	0.77
1850.0	37.42	0.73
1900.0	43.20	0.69
1950.0	52.24	0.67
2000.0	46.44	0.63
2050.0	41.52	0.62
2100.0	38.91	0.59
2150.0	37.36	0.58
2200.0	36.39	0.56
2250.0	35.84	0.55
2300.0	35.57	0.53
2350.0	35.52	0.52
2400.0	35.63	0.51
2450.0	35.89	0.50
2500.0	36.29	0.49
2550.0	36.80	0.49
2600.0	37.41	0.48
2650.0	38.16	0.47
2700.0	38.99	0.46
2725.0	39.47	0.46
2750.0	39.96	0.45
2775.0	40.50	0.45
2800.0	41.07	0.44
2900.0	43.91	0.44
3000.0	47.87	0.43
3100.0	52.85	0.42
3200.0	53.19	0.41
3300.0	48.59	0.41
3400.0	45.24	0.40
3500.0	43.07	0.39
4000.0	37.20	0.39
4500.0	34.55	0.41
5000.0	31.00	0.45
5240.0	28.62	0.47
5500.0	23.90	0.50
6000.0	6.87	2.83



P.O. Box 350168, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 934-4861 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine - Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/MICROWAVE COMPONENTS

REV. X1
LFCN-ED13263/2
1/7/2009
Page 1 of 1