

Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	VSWR (:1)	GROUP DELAY (ns)
1.0	0.04	1.00	0.46
5.0	0.04	1.00	0.46
10.0	0.03	1.00	0.49
30.0	0.04	1.01	0.47
50.0	0.06	1.02	0.46
100.0	0.08	1.05	0.46
300.0	0.18	1.16	0.45
500.0	0.26	1.23	0.46
700.0	0.32	1.21	0.49
900.0	0.36	1.08	0.53
1025.0	0.42	1.07	0.60
1075.0	0.47	1.13	0.65
1125.0	0.53	1.19	0.69
1175.0	0.60	1.26	0.74
1225.0	0.69	1.32	0.79
1275.0	0.80	1.35	0.86
1325.0	0.92	1.36	0.97
1375.0	1.08	1.32	1.12
1425.0	1.33	1.25	1.35
1450.0	1.54	1.22	1.61
1500.0	2.41	1.30	2.04
1550.0	5.66	2.19	2.96
1600.0	16.14	5.55	2.85
1800.0	40.74	25.62	0.49
2200.0	34.40	50.17	0.27
2300.0	30.57	52.42	0.32
2400.0	28.03	54.76	0.32
2500.0	26.20	56.69	0.31
2600.0	24.82	57.78	0.30
3000.0	21.46	54.87	0.28
4000.0	17.29	38.02	0.26