

Bi-Directional Coupler

MBDC-13-63HP+

Typical Performance Data

TEST CONDITIONS: INPUT POWER =+10 dBm @Temperature = -55°C

FREQ. (MHz)	INSERTION LOSS (dB)		COUPLING (dB)		DIRECTIVITY (dB)		RETURN LOSS (dB)			
	In - Out	Rev - Fwd	In Fwd	Rev - Out	In - Rev	Out - Fwd	In	Out	Rev	Fwd
1000	0.03	0.00	19.64	19.64	20.27	20.35	45.26	50.67	44.98	43.82
1200	0.03	0.01	18.19	18.19	20.25	20.29	41.20	47.02	40.82	43.83
1500	0.05	0.02	16.48	16.48	19.62	19.94	37.48	37.45	32.74	33.15
1800	0.06	0.04	15.18	15.18	19.60	19.78	28.93	28.25	27.93	27.53
1900	0.05	0.03	14.81	14.83	19.54	19.51	28.12	27.42	27.50	26.96
2000	0.07	0.04	14.47	14.49	18.86	19.09	27.12	26.44	26.50	26.20
2100	0.08	0.05	14.16	14.19	18.43	18.90	26.19	25.60	24.54	24.53
2200	0.08	0.06	13.89	13.91	18.61	18.89	25.27	24.73	23.70	23.41
2300	0.09	0.06	13.61	13.64	18.97	18.70	24.30	23.80	24.28	23.65
2400	0.10	0.06	13.36	13.39	18.28	18.52	23.40	22.87	23.03	23.01
2500	0.09	0.05	13.17	13.20	18.43	19.00	22.48	21.93	21.68	21.88
2600	0.10	0.05	13.00	13.03	18.92	19.60	21.63	21.07	21.61	21.48
2700	0.11	0.06	12.83	12.87	19.42	20.00	21.10	20.60	21.97	21.67
2800	0.11	0.06	12.66	12.69	19.84	20.37	21.02	20.64	22.40	21.93
2900	0.12	0.05	12.53	12.56	19.60	19.90	21.05	20.58	22.66	22.05
3000	0.12	0.05	12.38	12.41	19.88	19.93	21.05	20.57	22.74	22.22
3100	0.13	0.06	12.24	12.26	19.37	19.48	20.84	20.22	23.42	22.81
3200	0.14	0.05	12.19	12.22	19.35	19.08	20.65	20.11	24.44	23.62
3300	0.14	0.06	12.05	12.08	19.23	18.98	20.33	19.99	24.83	24.06
3400	0.17	0.07	11.98	12.02	18.96	19.04	20.03	19.86	24.76	24.42
3500	0.16	0.06	11.92	11.94	18.34	18.84	19.71	19.60	23.86	23.60
3600	0.14	0.08	11.86	11.89	19.00	19.51	19.52	19.57	22.97	22.87
3700	0.14	0.07	11.80	11.83	19.27	19.67	19.78	19.94	22.80	22.61
3800	0.13	0.05	11.77	11.79	19.98	20.43	20.20	20.46	23.04	22.88
3900	0.12	0.05	11.75	11.77	20.70	21.40	20.88	21.18	23.14	23.18
4000	0.13	0.08	11.82	11.83	20.53	21.00	21.72	21.99	22.52	22.79
4100	0.10	0.07	11.79	11.82	20.44	21.03	22.22	22.50	21.85	22.01
4200	0.11	0.07	11.83	11.89	20.13	20.80	22.63	22.87	21.99	22.02
4300	0.09	0.07	11.86	11.90	19.47	20.29	22.86	22.80	22.43	22.00
4400	0.10	0.06	11.92	11.94	18.78	19.85	22.74	22.47	22.21	21.91
4500	0.11	0.07	11.98	12.03	18.37	19.61	22.69	22.52	21.36	21.35
4600	0.12	0.08	12.03	12.05	17.98	19.23	23.19	23.32	20.93	20.67
4700	0.13	0.07	12.10	12.16	18.65	20.14	23.99	24.12	20.72	20.32
4800	0.13	0.08	12.17	12.20	19.19	21.51	25.35	24.93	20.87	20.27
4900	0.12	0.09	12.28	12.29	20.37	22.75	26.80	25.27	21.41	20.89
5000	0.11	0.08	12.35	12.38	21.90	24.18	28.76	26.23	20.94	20.53
5100	0.11	0.09	12.51	12.57	23.67	26.69	31.98	27.49	21.57	21.08
5200	0.10	0.08	12.60	12.63	25.87	29.53	36.57	27.72	22.89	22.22
5300	0.10	0.07	12.72	12.80	27.85	30.23	35.60	28.22	24.05	22.91
5400	0.10	0.05	12.94	12.99	32.32	33.47	33.13	28.88	25.86	24.00
5500	0.09	0.06	13.15	13.13	32.30	32.85	29.64	27.99	26.81	25.88
5600	0.09	0.06	13.31	13.35	32.09	30.65	27.95	26.31	27.24	27.03
5700	0.07	0.06	13.56	13.57	31.64	29.57	25.71	24.71	30.10	28.53
5800	0.06	0.05	13.76	13.77	27.27	25.47	24.27	23.81	35.64	31.72
5900	0.09	0.06	14.05	14.00	24.10	22.66	23.77	23.52	50.33	40.61
6000	0.08	0.05	14.20	14.22	20.01	20.36	24.01	24.09	43.19	43.39
6100	0.09	0.06	14.52	14.43	18.31	19.53	25.45	25.20	33.83	36.56
6200	0.10	0.05	14.77	14.77	17.33	18.36	27.56	25.82	32.00	35.34
6300	0.11	0.07	15.03	15.04	16.36	17.50	30.00	26.59	32.98	32.50
6400	0.12	0.09	15.31	15.37	16.47	17.14	34.75	26.45	28.80	28.45
6500	0.13	0.10	15.65	15.72	15.85	16.93	36.41	25.09	25.17	25.36
6700	0.14	0.12	16.42	16.54	14.10	15.71	28.93	23.03	21.73	21.75
6900	0.18	0.20	17.37	17.52	12.07	12.95	20.71	19.19	18.27	17.91
7000	0.21	0.24	18.05	18.17	11.78	12.24	18.48	17.42	16.50	16.24

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"). Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MC_Store/terms.jsp



Bi-Directional Coupler

MBDC-13-63HP+

Typical Performance Data

TEST CONDITIONS: INPUT POWER =+10 dBm @Temperature = +25°C

FREQ. (MHz)	INSERTION LOSS (dB)		COUPLING (dB)		DIRECTIVITY (dB)		RETURN LOSS (dB)			
	In - Out	Rev - Fwd	In Fwd	Rev - Out	In - Rev	Out - Fwd	In - Out - Rev - Fwd			
							In	Out	Rev	Fwd
1000	0.02	0.01	19.66	19.66	19.27	19.44	42.53	44.98	45.50	52.85
1200	0.02	0.01	18.21	18.21	18.94	18.99	45.75	52.04	43.58	44.27
1500	0.04	0.03	16.51	16.51	18.98	19.11	36.25	36.01	33.92	33.88
1800	0.05	0.04	15.21	15.22	18.18	18.41	28.58	28.35	27.79	27.69
1900	0.05	0.05	14.85	14.86	17.84	17.94	27.10	26.89	26.57	26.37
2000	0.06	0.05	14.51	14.53	17.44	17.53	25.49	25.23	25.48	25.21
2100	0.07	0.07	14.21	14.24	17.15	17.25	24.31	23.96	24.37	24.05
2200	0.08	0.07	13.92	13.96	16.87	17.08	23.24	22.81	23.19	22.97
2300	0.09	0.07	13.66	13.69	16.72	17.01	22.25	21.73	22.50	22.27
2400	0.09	0.08	13.43	13.47	16.64	17.05	21.42	20.95	21.78	21.60
2500	0.10	0.08	13.25	13.29	16.91	17.20	20.62	20.27	21.23	21.07
2600	0.11	0.08	13.07	13.11	17.00	17.35	19.90	19.66	20.72	20.60
2700	0.12	0.09	12.91	12.95	16.88	17.26	19.25	19.06	20.22	20.18
2800	0.14	0.11	12.79	12.83	16.73	17.20	18.84	18.72	19.93	19.84
2900	0.15	0.12	12.66	12.69	16.53	16.94	18.48	18.29	19.65	19.53
3000	0.15	0.12	12.54	12.56	16.37	16.72	18.33	18.10	19.45	19.37
3100	0.15	0.11	12.42	12.44	16.04	16.40	18.16	17.91	19.20	19.24
3200	0.17	0.13	12.33	12.35	15.91	16.20	18.00	17.80	19.17	19.17
3300	0.16	0.13	12.21	12.24	16.01	16.23	17.94	17.86	19.15	19.10
3400	0.17	0.15	12.12	12.15	16.08	16.31	17.83	17.82	19.11	19.14
3500	0.17	0.15	12.08	12.11	16.34	16.64	17.89	17.87	19.08	19.16
3600	0.16	0.14	12.03	12.05	16.91	17.23	17.97	17.82	19.07	19.25
3700	0.15	0.12	11.96	11.98	17.54	17.71	18.19	18.00	19.32	19.42
3800	0.15	0.10	11.92	11.93	18.19	18.17	18.53	18.40	19.62	19.62
3900	0.13	0.11	11.94	11.94	18.50	18.57	18.98	18.99	19.77	19.78
4000	0.11	0.11	11.94	11.96	18.74	18.93	19.25	19.49	19.92	20.06
4100	0.11	0.11	11.96	11.99	18.67	18.89	19.81	20.11	20.29	20.34
4200	0.11	0.11	12.00	12.02	18.89	19.06	20.43	20.77	20.79	20.78
4300	0.11	0.10	12.01	12.03	19.14	19.21	21.16	21.32	21.45	21.22
4400	0.11	0.10	12.07	12.09	19.47	19.69	22.10	22.14	21.92	21.85
4500	0.11	0.09	12.10	12.11	20.00	20.34	23.56	23.28	22.21	22.06
4600	0.12	0.10	12.17	12.18	21.12	21.61	25.52	25.12	22.82	22.31
4700	0.11	0.10	12.22	12.24	22.60	23.39	27.28	26.78	23.66	22.82
4800	0.11	0.11	12.29	12.31	24.02	25.19	28.74	28.46	24.34	23.60
4900	0.09	0.10	12.38	12.40	26.59	28.61	30.38	31.13	25.35	24.79
5000	0.09	0.10	12.48	12.50	27.81	31.34	33.05	34.43	25.32	25.17
5100	0.09	0.11	12.61	12.64	29.13	33.49	38.93	38.08	25.57	25.51
5200	0.09	0.10	12.74	12.79	31.35	33.87	49.61	38.31	26.98	26.33
5300	0.09	0.09	12.93	12.96	32.90	34.82	39.89	37.97	28.85	27.64
5400	0.08	0.10	13.13	13.13	32.34	35.41	35.51	35.77	29.46	28.20
5500	0.08	0.10	13.32	13.33	30.43	34.28	32.66	31.97	28.73	28.57
5600	0.09	0.12	13.53	13.50	27.37	30.48	31.83	30.89	28.04	28.35
5700	0.10	0.13	13.71	13.71	25.44	28.19	31.46	30.32	28.08	28.59
5800	0.10	0.12	13.94	13.97	24.53	25.91	32.70	30.31	28.93	29.16
5900	0.11	0.12	14.20	14.20	24.19	24.31	33.23	29.74	28.55	28.73
6000	0.12	0.13	14.45	14.48	23.35	23.48	34.00	30.22	26.64	27.08
6100	0.12	0.13	14.72	14.72	22.16	22.63	35.16	30.66	25.50	25.83
6200	0.12	0.14	15.00	15.00	21.42	22.43	39.02	31.13	25.19	24.98
6300	0.12	0.13	15.31	15.30	21.24	22.32	43.65	32.20	25.08	24.29
6400	0.13	0.15	15.60	15.65	20.92	21.68	37.48	31.08	23.79	23.14
6500	0.15	0.17	15.99	16.02	19.73	21.11	33.71	29.35	21.94	22.25
6700	0.16	0.21	16.81	16.85	16.70	17.91	26.27	25.60	20.73	20.75
6900	0.19	0.23	17.76	17.81	14.20	15.39	21.20	20.87	18.95	18.88
7000	0.22	0.24	18.39	18.40	13.36	14.14	20.02	19.60	17.82	17.83

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp



Bi-Directional Coupler

MBDC-13-63HP+

Typical Performance Data

TEST CONDITIONS: INPUT POWER =+10 dBm @Temperature = +105°C

FREQ. (MHz)	INSERTION LOSS (dB)		COUPLING (dB)		DIRECTIVITY (dB)		RETURN LOSS (dB)			
	In - Out	Rev - Fwd	In Fwd	Rev - Out	In - Rev	Out - Fwd	In	Out	Rev	Fwd
1000	0.04	0.04	19.76	19.74	22.35	23.96	32.28	30.74	30.53	30.01
1200	0.05	0.06	18.32	18.29	22.50	25.04	32.78	31.25	30.59	30.06
1500	0.05	0.06	16.63	16.61	22.76	26.21	33.22	32.87	30.51	29.90
1800	0.06	0.07	15.33	15.31	22.50	26.02	33.24	33.61	29.97	29.43
1900	0.07	0.07	14.98	14.96	22.46	25.73	33.12	33.48	29.61	29.10
2000	0.07	0.08	14.64	14.61	22.21	25.02	32.30	32.83	28.83	28.30
2100	0.07	0.09	14.33	14.32	22.13	24.63	30.93	31.36	28.20	27.76
2200	0.08	0.09	14.06	14.05	22.15	24.31	29.41	29.74	27.63	27.37
2300	0.08	0.08	13.80	13.79	22.28	23.89	28.26	28.65	27.18	27.00
2400	0.08	0.08	13.57	13.56	22.53	23.59	27.24	27.49	26.84	26.78
2500	0.08	0.09	13.35	13.33	22.74	23.23	26.38	26.49	26.76	26.82
2600	0.10	0.10	13.20	13.17	23.26	23.46	25.84	25.83	27.21	27.25
2700	0.11	0.11	13.00	12.99	23.86	23.31	24.85	24.96	27.27	27.64
2800	0.11	0.10	12.86	12.84	24.55	23.46	24.27	24.17	27.90	28.09
2900	0.11	0.09	12.72	12.69	25.08	23.27	23.76	23.66	28.22	28.53
3000	0.11	0.10	12.58	12.54	25.76	23.47	23.52	23.25	29.21	29.51
3100	0.13	0.09	12.47	12.43	26.36	23.59	23.40	23.22	30.26	31.15
3200	0.13	0.11	12.38	12.35	26.55	23.38	23.79	23.27	32.49	33.08
3300	0.13	0.11	12.31	12.28	28.74	24.01	24.21	23.77	35.73	36.85
3400	0.11	0.11	12.23	12.20	31.71	24.69	24.75	24.16	41.52	45.00
3500	0.12	0.11	12.16	12.13	35.32	25.19	25.57	24.92	53.75	55.55
3600	0.11	0.11	12.11	12.07	39.53	25.69	26.65	25.85	47.93	43.16
3700	0.13	0.12	12.08	12.04	42.53	25.78	28.27	26.84	39.78	37.73
3800	0.12	0.12	12.07	12.03	43.32	27.76	29.86	28.39	36.06	34.31
3900	0.14	0.14	12.06	12.03	39.59	27.10	32.40	30.24	33.58	32.86
4000	0.11	0.13	12.09	12.05	34.47	29.62	35.87	33.11	32.03	31.41
4100	0.12	0.13	12.12	12.09	31.35	31.44	35.99	34.17	30.44	30.35
4200	0.13	0.13	12.14	12.12	28.78	32.99	32.35	32.86	29.41	29.52
4300	0.13	0.15	12.18	12.14	26.23	33.40	29.62	30.53	28.83	29.31
4400	0.13	0.15	12.25	12.19	24.63	33.01	27.43	28.33	28.84	29.34
4500	0.13	0.15	12.33	12.27	23.20	31.53	25.56	26.13	28.94	29.64
4600	0.13	0.17	12.43	12.39	22.58	30.82	24.34	24.76	29.27	30.63
4700	0.16	0.19	12.49	12.44	20.86	27.56	23.09	23.95	30.00	32.42
4800	0.16	0.17	12.62	12.55	19.85	26.28	21.90	22.97	31.01	33.92
4900	0.14	0.18	12.71	12.61	18.57	24.01	21.63	22.48	31.58	37.04
5000	0.15	0.17	12.87	12.77	18.22	23.16	21.38	22.27	31.45	40.93
5100	0.17	0.18	13.07	12.91	17.79	22.18	21.62	22.35	32.41	38.74
5200	0.14	0.19	13.15	13.03	16.78	20.40	22.11	23.04	31.28	34.96
5300	0.17	0.20	13.34	13.20	16.44	19.72	22.89	24.23	30.48	31.85
5400	0.16	0.20	13.52	13.41	16.17	18.96	24.26	25.66	28.32	28.52
5500	0.17	0.22	13.70	13.56	15.71	18.01	26.84	28.76	25.89	25.94
5600	0.17	0.23	13.86	13.79	14.94	16.71	29.17	32.78	24.03	24.02
5700	0.20	0.25	14.13	14.01	14.30	16.03	30.89	41.04	22.33	22.14
5800	0.17	0.24	14.28	14.25	13.96	15.36	30.82	34.60	21.03	20.68
5900	0.17	0.27	14.51	14.57	13.75	14.62	26.57	27.15	19.96	19.70
6000	0.20	0.27	14.86	14.91	13.43	13.81	23.19	23.25	18.99	18.76
6100	0.23	0.28	15.19	15.14	13.21	13.39	20.31	20.28	18.26	18.06
6200	0.24	0.30	15.49	15.54	12.98	12.58	18.12	18.12	17.40	17.26
6300	0.30	0.32	15.92	15.93	12.56	12.07	16.38	16.50	16.61	16.50
6400	0.34	0.34	16.31	16.38	12.17	11.20	15.04	15.07	15.87	15.79
6500	0.39	0.37	16.72	16.88	11.75	10.84	13.93	13.86	15.22	15.16
6700	0.51	0.42	17.76	17.84	11.15	10.08	12.12	12.03	14.08	14.11
6900	0.63	0.45	18.96	19.14	10.25	8.86	10.72	10.56	13.44	13.44
7000	0.70	0.47	19.64	19.84	10.16	8.09	10.17	9.98	13.06	13.16

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"). Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MC_Store/terms.jsp

