



Typical Performance Curves


GAIN vs. FREQUENCY & TEMPERATURE
INPUT POWER = -25dBm, Vd = 5V




GAIN vs. FREQUENCY & DEVICE VOLTAGE
INPUT POWER = -25dBm, Temperature = +25°C




ISOLATION vs. FREQUENCY & TEMPERATURE
INPUT POWER = -25dBm, Vd = 5V




ISOLATION vs. FREQUENCY & DEVICE VOLTAGE
INPUT POWER = -25dBm, Temperature = +25°C




INPUT RETURN LOSS vs. FREQUENCY & TEMPERATURE
INPUT POWER = -25dBm, Vd = 5V




INPUT RETURN LOSS vs. FREQUENCY & DEVICE VOLTAGE
INPUT POWER = -25dBm, Temperature = +25°C



OUTPUT RETURN LOSS vs. FREQUENCY & TEMPERATURE
INPUT POWER = -25dBm, Vd = 5V




OUTPUT RETURN LOSS vs. FREQUENCY & DEVICE VOLTAGE
INPUT POWER = -25dBm, Temperature = +25°C




Typical Performance Curves


OUTPUT IP3 vs. FREQUENCY & TEMPERATURE
 OUTPUT POWER = 0 dBm/tone, Vd = 5V




OUTPUT IP3 vs. FREQUENCY & DEVICE VOLTAGE
 OUTPUT POWER = 0 dBm/tone, Temperature = +25°C




P1dB vs. FREQUENCY & TEMPERATURE
 Vd = 5V




P1dB vs. FREQUENCY & DEVICE VOLTAGE
 Temperature = +25°C



NOISE FIGURE vs. FREQUENCY & TEMPERATURE
 Vd = 5V



NOISE FIGURE vs. FREQUENCY & DEVICE VOLTAGE
 Temperature = +25°C



GAIN VARIATION vs. FREQUENCY & TEMPERATURE
 INPUT POWER = -25dBm, Vd = 5V

