

Typical Performance Data

NOTE: Use PDF Bookmarks to view DATA at required conditions

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 3.00V, Id = 71.08mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	22.70	26.01	10.64	15.59	1.03	0.54	32.50	15.45	1.08
30	22.40	25.47	12.17	16.17	1.03	0.51	33.73	16.92	1.02
40	22.19	25.22	13.05	15.61	1.03	0.49	34.84	18.03	1.00
50	22.04	25.07	13.58	15.23	1.03	0.48	34.62	18.50	0.96
60	21.97	25.01	13.99	15.06	1.04	0.48	34.80	18.62	1.01
70	21.90	24.96	14.21	14.94	1.04	0.47	34.73	18.67	0.98
80	21.86	24.93	14.35	14.85	1.04	0.47	34.41	18.78	0.94
90	21.83	24.91	14.41	14.82	1.04	0.47	34.24	18.85	1.04
100	21.80	24.90	14.45	14.79	1.04	0.48	34.33	18.76	0.96
150	21.71	24.90	14.20	14.92	1.05	0.49	34.31	18.91	0.94
200	21.63	24.94	13.75	15.24	1.05	0.51	34.49	18.99	0.93
250	21.55	25.00	13.13	15.67	1.05	0.53	34.32	19.06	0.96
300	21.46	25.07	12.48	16.19	1.05	0.56	34.58	19.00	0.97
350	21.37	25.17	11.88	16.84	1.06	0.59	34.24	19.05	0.96
400	21.26	25.27	11.30	17.61	1.06	0.63	33.90	18.95	1.00
450	21.14	25.37	10.76	18.64	1.07	0.66	33.55	18.94	0.98
500	21.03	25.49	10.25	19.82	1.07	0.70	33.31	18.82	1.03
550	20.90	25.62	9.83	21.40	1.08	0.73	33.16	18.72	1.08
600	20.78	25.76	9.43	23.22	1.08	0.77	32.66	18.84	1.22
650	20.64	25.90	9.06	25.45	1.09	0.80	32.37	18.60	1.14
700	20.50	26.05	8.72	27.37	1.10	0.84	32.07	18.73	1.10
750	20.35	26.21	8.44	28.09	1.11	0.87	31.88	18.71	1.14
800	20.20	26.37	8.19	26.42	1.12	0.90	31.75	18.67	1.09
850	20.06	26.51	7.96	24.28	1.12	0.92	31.34	18.36	1.17
900	19.93	26.65	7.77	22.17	1.13	0.94	31.25	18.39	1.15
950	19.80	26.78	7.61	20.41	1.14	0.96	31.15	18.72	1.15
1000	19.66	26.92	7.46	18.89	1.15	0.98	30.87	18.68	1.21
1100	19.40	27.17	7.30	16.41	1.16	1.01	30.78	18.29	1.16
1200	19.14	27.38	7.22	14.56	1.18	1.02	30.44	18.45	1.24
1300	18.89	27.56	7.25	13.17	1.19	1.03	30.44	18.46	1.27
1400	18.65	27.72	7.35	12.05	1.21	1.03	30.23	18.17	1.32
1500	18.42	27.83	7.48	11.16	1.22	1.02	29.91	18.22	1.33
1600	18.18	27.97	7.59	10.43	1.23	1.02	29.86	18.10	1.42
1700	17.92	28.07	7.61	9.84	1.24	1.02	29.41	18.03	1.40
1800	17.62	28.21	7.46	9.39	1.25	1.03	29.55	17.80	1.45
1900	17.26	28.41	7.12	9.04	1.26	1.05	29.46	17.72	1.52
2000	16.83	28.64	6.57	8.77	1.28	1.08	29.11	17.69	1.61
2100	16.33	28.92	5.87	8.56	1.29	1.12	28.97	17.58	1.75
2200	15.76	29.28	5.13	8.40	1.30	1.16	28.50	17.51	1.96
2300	15.09	29.69	4.43	8.30	1.33	1.21	28.50	17.25	2.14
2400	14.38	30.19	3.80	8.19	1.36	1.26	28.12	17.06	2.33
2500	13.60	30.71	3.25	8.11	1.40	1.30	28.37	17.03	2.60

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.00V, Id = 140.45mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	23.44	26.53	10.57	14.50	1.02	0.50	41.12	21.53	1.11
30	23.09	26.02	11.72	14.37	1.02	0.47	42.41	22.57	1.05
40	22.86	25.79	12.27	13.76	1.03	0.45	44.43	23.27	1.01
50	22.70	25.70	12.51	13.40	1.03	0.45	41.45	23.62	0.99
60	22.63	25.60	12.84	13.25	1.03	0.44	43.59	23.61	1.02
70	22.56	25.56	12.97	13.13	1.03	0.44	42.21	23.57	0.97
80	22.52	25.53	13.05	13.04	1.04	0.44	41.75	23.68	0.95
90	22.48	25.51	13.09	13.01	1.04	0.44	42.44	23.77	0.97
100	22.46	25.50	13.14	12.97	1.04	0.44	41.75	23.62	0.96
150	22.37	25.48	13.11	13.03	1.04	0.45	41.89	23.76	1.03
200	22.32	25.51	13.00	13.21	1.04	0.46	41.89	23.90	0.92
250	22.26	25.56	12.76	13.46	1.05	0.48	41.65	24.01	0.96
300	22.20	25.61	12.48	13.75	1.05	0.50	41.62	23.95	0.96
350	22.14	25.68	12.22	14.10	1.05	0.52	41.29	24.03	0.94
400	22.07	25.76	11.92	14.50	1.06	0.54	40.45	23.93	1.03
450	21.99	25.84	11.63	15.02	1.07	0.57	39.94	23.97	1.01
500	21.92	25.94	11.34	15.58	1.07	0.60	39.54	23.83	1.03
550	21.84	26.03	11.08	16.28	1.08	0.62	39.49	23.73	1.05
600	21.77	26.14	10.83	17.01	1.08	0.65	38.80	23.91	1.43
650	21.68	26.26	10.59	17.83	1.09	0.68	38.62	23.60	1.18
700	21.58	26.39	10.35	18.58	1.10	0.71	38.47	23.82	1.11
750	21.49	26.53	10.15	19.34	1.11	0.73	38.00	23.80	1.13
800	21.39	26.67	9.97	19.88	1.12	0.76	37.92	23.73	1.08
850	21.30	26.82	9.81	20.36	1.13	0.78	37.26	23.36	1.15
900	21.21	26.95	9.64	20.47	1.14	0.80	37.00	23.38	1.12
950	21.12	27.09	9.50	20.27	1.15	0.82	37.50	23.85	1.12
1000	21.03	27.23	9.38	19.74	1.16	0.84	37.84	23.79	1.18
1100	20.85	27.53	9.23	18.13	1.19	0.87	36.59	23.23	1.12
1200	20.66	27.83	9.19	16.42	1.21	0.89	36.56	23.48	1.23
1300	20.48	28.12	9.24	14.95	1.24	0.91	36.35	23.50	1.25
1400	20.31	28.40	9.38	13.72	1.27	0.91	35.73	23.00	1.28
1500	20.13	28.65	9.58	12.70	1.30	0.92	35.78	23.11	1.29
1600	19.95	28.93	9.77	11.85	1.33	0.93	35.61	23.07	1.35
1700	19.77	29.17	9.86	11.15	1.35	0.93	35.18	23.02	1.35
1800	19.54	29.43	9.73	10.59	1.37	0.95	35.06	22.83	1.38
1900	19.27	29.73	9.32	10.13	1.40	0.97	35.04	22.80	1.49
2000	18.94	30.06	8.59	9.75	1.42	1.00	34.93	22.91	1.53
2100	18.55	30.40	7.62	9.42	1.43	1.04	34.81	22.81	1.70
2200	18.09	30.81	6.62	9.14	1.44	1.09	34.83	22.94	1.85
2300	17.53	31.22	5.66	8.93	1.45	1.14	34.24	22.42	2.02
2400	16.93	31.73	4.80	8.69	1.47	1.19	33.82	22.12	2.19
2500	16.24	32.21	4.06	8.49	1.48	1.24	34.27	22.35	2.43

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 2.70V, Id =62.12mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	22.38	25.80	10.61	15.92	1.04	0.55	30.39	14.45	1.08
30	22.11	25.25	12.37	17.09	1.03	0.52	32.42	15.91	1.03
40	21.92	24.99	13.45	16.71	1.04	0.50	33.29	17.02	1.00
50	21.79	24.89	14.19	16.42	1.04	0.50	33.06	17.49	0.96
60	21.72	24.78	14.64	16.26	1.04	0.49	33.12	17.62	1.00
70	21.66	24.74	14.93	16.14	1.04	0.49	33.18	17.66	0.99
80	21.63	24.71	15.09	16.06	1.04	0.49	32.95	17.77	0.97
90	21.59	24.69	15.18	16.04	1.04	0.49	32.74	17.86	0.94
100	21.57	24.68	15.21	16.02	1.04	0.49	32.90	17.75	0.97
150	21.48	24.68	14.87	16.22	1.05	0.50	32.91	17.90	0.97
200	21.40	24.72	14.21	16.61	1.05	0.52	32.89	17.97	0.95
250	21.31	24.79	13.44	17.17	1.05	0.55	32.80	18.04	0.94
300	21.22	24.87	12.68	17.87	1.06	0.58	32.87	17.98	1.03
350	21.12	24.96	11.98	18.78	1.06	0.61	32.38	18.01	0.97
400	21.01	25.07	11.29	19.85	1.06	0.65	32.30	17.89	1.00
450	20.88	25.19	10.67	21.23	1.07	0.68	31.97	17.89	1.02
500	20.76	25.31	10.12	22.85	1.07	0.72	31.42	17.76	1.04
550	20.63	25.45	9.63	24.88	1.08	0.76	31.27	17.65	1.06
600	20.49	25.59	9.19	26.88	1.08	0.79	30.90	17.79	1.09
650	20.35	25.74	8.78	28.14	1.09	0.83	30.60	17.54	1.16
700	20.19	25.90	8.43	27.31	1.10	0.86	30.31	17.67	1.08
750	20.04	26.06	8.14	25.26	1.10	0.89	30.18	17.63	1.11
800	19.88	26.22	7.88	22.90	1.11	0.92	30.09	17.60	1.12
850	19.74	26.37	7.65	20.92	1.12	0.94	29.66	17.28	1.18
900	19.59	26.50	7.45	19.25	1.12	0.96	29.57	17.32	1.14
950	19.46	26.63	7.29	17.87	1.13	0.98	29.54	17.64	1.19
1000	19.31	26.75	7.16	16.71	1.13	0.99	29.36	17.57	1.23
1100	19.04	26.97	7.00	14.75	1.15	1.01	29.18	17.23	1.16
1200	18.77	27.16	6.96	13.22	1.16	1.02	28.86	17.39	1.23
1300	18.52	27.30	7.02	12.03	1.17	1.02	28.93	17.34	1.32
1400	18.28	27.42	7.16	11.05	1.18	1.02	28.65	17.07	1.32
1500	18.03	27.50	7.36	10.26	1.19	1.01	28.36	17.14	1.33
1600	17.79	27.62	7.53	9.62	1.20	1.01	28.35	16.98	1.42
1700	17.53	27.69	7.59	9.10	1.21	1.00	27.92	16.89	1.41
1800	17.22	27.78	7.48	8.73	1.21	1.01	28.03	16.66	1.44
1900	16.85	27.96	7.16	8.42	1.23	1.03	27.93	16.55	1.55
2000	16.40	28.21	6.59	8.25	1.25	1.06	27.61	16.56	1.61
2100	15.88	28.47	5.84	8.11	1.25	1.10	27.46	16.40	1.76
2200	15.27	28.85	5.07	8.04	1.27	1.15	27.09	16.35	1.97
2300	14.56	29.27	4.33	8.01	1.29	1.21	27.04	16.08	2.15
2400	13.81	29.78	3.67	7.98	1.33	1.26	26.68	15.88	2.36
2500	13.00	30.35	3.12	7.94	1.37	1.31	26.92	15.84	2.67

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.25V, Id = 149.05mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	23.48	26.55	10.57	14.48	1.02	0.49	41.55	22.07	1.11
30	23.14	26.05	11.69	14.32	1.02	0.47	42.19	22.98	1.02
40	22.90	25.82	12.21	13.70	1.03	0.45	44.00	23.68	1.01
50	22.74	25.74	12.56	13.34	1.03	0.45	43.81	24.02	0.97
60	22.67	25.63	12.75	13.18	1.03	0.44	43.42	24.03	1.03
70	22.60	25.59	12.88	13.06	1.03	0.44	42.19	23.98	0.96
80	22.56	25.56	12.95	12.98	1.04	0.44	43.21	24.10	0.97
90	22.52	25.54	13.01	12.94	1.04	0.43	42.75	24.18	0.97
100	22.50	25.53	13.05	12.91	1.04	0.44	42.63	24.04	0.97
150	22.42	25.52	13.04	12.96	1.04	0.44	42.08	24.18	0.95
200	22.36	25.55	12.93	13.13	1.04	0.46	42.75	24.32	0.93
250	22.30	25.59	12.72	13.36	1.05	0.47	42.84	24.43	0.94
300	22.24	25.65	12.46	13.62	1.05	0.49	40.75	24.39	0.98
350	22.19	25.71	12.23	13.96	1.05	0.51	41.61	24.46	0.94
400	22.12	25.79	11.94	14.32	1.06	0.54	40.82	24.37	1.04
450	22.05	25.87	11.66	14.80	1.07	0.56	40.36	24.40	0.99
500	21.98	25.97	11.39	15.31	1.07	0.59	40.15	24.27	1.03
550	21.90	26.07	11.15	15.95	1.08	0.62	39.65	24.18	1.05
600	21.83	26.18	10.91	16.59	1.08	0.64	39.63	24.36	1.08
650	21.74	26.29	10.68	17.31	1.09	0.67	39.01	24.05	1.19
700	21.65	26.42	10.46	17.95	1.10	0.70	38.79	24.28	1.06
750	21.56	26.56	10.28	18.58	1.11	0.72	38.56	24.26	1.02
800	21.46	26.71	10.10	19.02	1.12	0.75	38.25	24.21	1.06
850	21.37	26.85	9.93	19.41	1.13	0.77	37.61	23.83	1.14
900	21.29	26.98	9.78	19.51	1.14	0.79	37.36	23.85	1.12
950	21.21	27.13	9.64	19.36	1.15	0.81	37.94	24.33	1.10
1000	21.12	27.28	9.52	18.94	1.17	0.83	38.11	24.27	1.20
1100	20.94	27.58	9.38	17.60	1.19	0.86	36.99	23.72	1.10
1200	20.76	27.89	9.34	16.09	1.22	0.88	37.02	23.95	1.21
1300	20.58	28.20	9.39	14.73	1.25	0.89	36.83	23.97	1.21
1400	20.41	28.50	9.53	13.56	1.28	0.90	36.09	23.46	1.26
1500	20.24	28.77	9.75	12.59	1.31	0.91	36.10	23.56	1.27
1600	20.07	29.08	9.94	11.76	1.34	0.92	36.09	23.51	1.34
1700	19.89	29.34	10.05	11.08	1.37	0.93	35.56	23.48	1.35
1800	19.67	29.63	9.92	10.52	1.39	0.94	35.39	23.30	1.37
1900	19.40	29.96	9.50	10.06	1.42	0.96	35.40	23.27	1.49
2000	19.08	30.31	8.75	9.68	1.44	0.99	35.35	23.38	1.55
2100	18.70	30.67	7.77	9.34	1.46	1.03	35.30	23.27	1.68
2200	18.24	31.10	6.75	9.03	1.47	1.08	35.28	23.39	1.85
2300	17.69	31.52	5.76	8.81	1.49	1.13	34.72	22.85	2.00
2400	17.10	32.04	4.89	8.55	1.50	1.18	34.15	22.55	2.17
2500	16.42	32.53	4.14	8.32	1.51	1.23	34.53	22.80	2.45

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 3.00V, Id = 69.49mA @ Temperature = -45°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	22.79	26.01	10.58	15.60	1.03	0.52	32.48	15.41	0.82
30	22.49	25.47	12.11	16.33	1.03	0.50	33.91	16.91	0.80
40	22.28	25.21	13.02	15.85	1.03	0.48	34.84	18.09	0.78
50	22.14	25.12	13.65	15.55	1.03	0.48	34.72	18.58	0.74
60	22.07	25.00	14.07	15.43	1.03	0.47	34.74	18.73	0.78
70	22.01	24.95	14.34	15.36	1.04	0.46	34.73	18.79	0.74
80	21.97	24.92	14.54	15.33	1.04	0.46	34.46	18.89	0.73
90	21.94	24.90	14.68	15.36	1.04	0.46	34.45	18.97	0.74
100	21.92	24.88	14.81	15.38	1.04	0.46	34.47	18.88	0.70
150	21.84	24.86	14.81	15.68	1.04	0.47	34.37	19.04	0.82
200	21.77	24.90	14.38	15.83	1.05	0.49	34.15	19.12	0.71
250	21.69	24.96	13.61	15.89	1.05	0.51	34.08	19.19	0.72
300	21.61	25.04	12.85	16.03	1.05	0.53	34.20	19.14	0.74
350	21.52	25.13	12.21	16.41	1.05	0.56	33.92	19.16	0.73
400	21.43	25.23	11.68	17.02	1.06	0.59	33.46	19.07	0.79
450	21.33	25.33	11.20	17.92	1.06	0.63	33.11	19.06	0.78
500	21.23	25.44	10.74	18.98	1.07	0.66	32.80	18.94	0.80
550	21.13	25.55	10.32	20.36	1.07	0.69	32.51	18.86	0.81
600	21.02	25.68	9.93	21.91	1.08	0.73	32.13	18.98	0.96
650	20.90	25.81	9.59	23.62	1.08	0.76	31.85	18.75	0.92
700	20.78	25.95	9.28	24.79	1.09	0.79	31.63	18.89	0.81
750	20.66	26.10	8.98	24.96	1.10	0.82	31.44	18.88	0.83
800	20.52	26.26	8.69	23.90	1.11	0.84	31.29	18.84	0.83
850	20.39	26.42	8.44	22.60	1.12	0.87	30.86	18.53	0.89
900	20.27	26.56	8.22	21.29	1.13	0.89	30.77	18.56	0.88
950	20.17	26.68	8.09	20.13	1.13	0.91	30.72	18.88	0.85
1000	20.06	26.81	7.99	19.01	1.14	0.93	30.53	18.81	0.91
1100	19.84	27.07	7.81	16.87	1.16	0.95	30.30	18.47	0.85
1200	19.60	27.32	7.68	15.12	1.17	0.97	30.00	18.61	0.95
1300	19.38	27.54	7.70	13.72	1.19	0.99	29.98	18.57	0.98
1400	19.17	27.74	7.77	12.58	1.20	0.99	29.67	18.29	1.00
1500	18.95	27.90	7.87	11.64	1.22	0.99	29.42	18.36	1.00
1600	18.74	28.08	7.98	10.85	1.23	0.99	29.35	18.24	1.09
1700	18.51	28.21	8.02	10.18	1.24	1.00	28.91	18.14	1.07
1800	18.25	28.37	7.93	9.68	1.25	1.01	28.94	17.90	1.10
1900	17.93	28.58	7.58	9.29	1.26	1.03	28.83	17.82	1.18
2000	17.54	28.83	6.97	8.98	1.26	1.06	28.53	17.79	1.21
2100	17.09	29.11	6.21	8.75	1.26	1.10	28.41	17.68	1.34
2200	16.57	29.46	5.44	8.56	1.27	1.15	28.02	17.62	1.50
2300	15.95	29.85	4.69	8.39	1.28	1.19	27.90	17.31	1.61
2400	15.29	30.32	4.03	8.21	1.29	1.24	27.54	17.11	1.75
2500	14.57	30.82	3.43	8.08	1.31	1.29	27.77	17.06	1.99

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.00V, Id = 141.13mA @ Temperature = -45°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	23.51	26.41	10.53	14.96	1.02	0.48	41.63	21.53	0.86
30	23.17	25.92	11.71	14.96	1.02	0.45	42.96	22.79	0.81
40	22.93	25.69	12.34	14.36	1.02	0.44	42.54	23.55	0.80
50	22.78	25.58	12.69	14.02	1.02	0.44	44.04	23.95	0.76
60	22.70	25.50	13.06	13.90	1.03	0.43	45.27	23.90	0.79
70	22.64	25.45	13.25	13.81	1.03	0.43	44.93	23.86	0.73
80	22.60	25.43	13.41	13.77	1.03	0.43	44.25	23.96	0.75
90	22.57	25.40	13.52	13.78	1.03	0.42	43.25	24.07	0.74
100	22.55	25.39	13.63	13.78	1.03	0.42	43.08	23.89	0.73
150	22.48	25.37	13.85	13.95	1.04	0.43	41.99	24.05	0.82
200	22.43	25.39	13.70	13.95	1.04	0.44	42.33	24.19	0.70
250	22.37	25.45	13.27	13.83	1.04	0.45	42.67	24.30	0.71
300	22.31	25.51	12.84	13.75	1.05	0.47	41.08	24.21	0.71
350	22.25	25.59	12.55	13.85	1.05	0.49	41.78	24.25	0.70
400	22.20	25.66	12.31	14.08	1.06	0.51	40.67	24.15	0.75
450	22.14	25.73	12.11	14.45	1.06	0.53	40.11	24.18	0.80
500	22.09	25.83	11.89	14.84	1.07	0.55	39.48	24.04	0.79
550	22.03	25.92	11.67	15.29	1.07	0.57	38.66	23.94	0.80
600	21.97	26.02	11.48	15.69	1.08	0.60	38.72	24.15	1.01
650	21.90	26.13	11.29	16.09	1.08	0.62	38.22	23.82	0.92
700	21.83	26.26	11.11	16.35	1.09	0.64	38.44	24.08	0.79
750	21.75	26.40	10.91	16.48	1.10	0.66	38.00	24.09	0.86
800	21.67	26.55	10.70	16.40	1.11	0.69	38.00	24.01	0.81
850	21.58	26.70	10.50	16.31	1.12	0.71	36.92	23.60	0.87
900	21.51	26.84	10.34	16.20	1.13	0.72	36.78	23.64	0.85
950	21.45	26.99	10.24	16.08	1.14	0.74	37.70	24.20	0.83
1000	21.39	27.13	10.17	15.90	1.15	0.76	37.86	24.17	0.94
1100	21.25	27.46	10.05	15.25	1.18	0.79	36.51	23.51	0.85
1200	21.09	27.81	9.94	14.37	1.21	0.81	36.75	23.81	0.90
1300	20.95	28.17	10.01	13.52	1.24	0.83	36.39	23.85	0.94
1400	20.80	28.53	10.15	12.69	1.27	0.85	35.53	23.26	0.98
1500	20.65	28.89	10.35	11.89	1.31	0.86	35.72	23.44	1.00
1600	20.50	29.29	10.56	11.20	1.35	0.87	35.60	23.38	1.04
1700	20.36	29.65	10.74	10.60	1.38	0.88	35.28	23.37	1.04
1800	20.18	30.04	10.74	10.08	1.42	0.89	34.74	23.17	1.06
1900	19.95	30.49	10.35	9.62	1.46	0.91	34.66	23.16	1.13
2000	19.68	30.96	9.51	9.21	1.49	0.95	34.95	23.32	1.20
2100	19.35	31.44	8.44	8.84	1.52	0.98	34.86	23.28	1.31
2200	18.95	31.97	7.33	8.51	1.54	1.03	35.29	23.49	1.44
2300	18.47	32.48	6.27	8.19	1.55	1.08	34.01	22.82	1.57
2400	17.93	33.06	5.34	7.81	1.57	1.12	33.47	22.51	1.69
2500	17.32	33.62	4.51	7.47	1.57	1.16	33.98	22.81	1.87

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 2.70V, Id = 58.08mA @ Temperature = -45°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	22.45	25.82	10.50	15.82	1.03	0.54	30.43	14.43	0.85
30	22.19	25.26	12.27	17.18	1.03	0.51	32.25	15.91	0.83
40	22.00	25.00	13.39	16.93	1.03	0.50	32.96	17.05	0.81
50	21.87	24.88	14.00	16.73	1.04	0.49	32.98	17.53	0.75
60	21.81	24.79	14.68	16.65	1.04	0.48	32.98	17.67	0.78
70	21.76	24.74	15.04	16.62	1.04	0.48	32.99	17.74	0.76
80	21.72	24.71	15.27	16.62	1.04	0.48	32.90	17.86	0.75
90	21.69	24.69	15.43	16.67	1.04	0.48	32.70	17.93	0.73
100	21.67	24.68	15.53	16.72	1.04	0.48	32.73	17.85	0.75
150	21.60	24.66	15.48	17.15	1.05	0.49	32.71	18.00	0.72
200	21.53	24.70	14.86	17.36	1.05	0.51	32.60	18.07	0.72
250	21.45	24.77	13.95	17.48	1.05	0.53	32.39	18.14	0.70
300	21.36	24.85	13.08	17.75	1.05	0.56	32.59	18.07	0.72
350	21.27	24.94	12.39	18.38	1.06	0.59	32.12	18.10	0.76
400	21.17	25.03	11.77	19.30	1.06	0.62	31.94	18.01	0.77
450	21.06	25.14	11.19	20.55	1.06	0.65	31.53	17.99	0.79
500	20.95	25.26	10.63	21.99	1.07	0.69	31.07	17.88	0.79
550	20.83	25.39	10.11	23.68	1.07	0.72	30.95	17.79	0.82
600	20.71	25.53	9.66	25.29	1.08	0.76	30.60	17.90	0.93
650	20.58	25.67	9.23	26.12	1.08	0.79	30.33	17.69	0.89
700	20.45	25.82	8.87	25.47	1.09	0.82	30.06	17.82	0.84
750	20.31	25.98	8.54	23.98	1.10	0.85	29.92	17.79	0.92
800	20.15	26.15	8.24	22.20	1.11	0.88	29.82	17.74	0.84
850	20.01	26.31	7.97	20.59	1.12	0.90	29.42	17.44	0.92
900	19.89	26.44	7.75	19.23	1.12	0.92	29.36	17.48	0.88
950	19.77	26.57	7.60	18.05	1.13	0.94	29.31	17.75	0.88
1000	19.65	26.69	7.48	17.02	1.13	0.95	29.05	17.72	0.96
1100	19.41	26.94	7.30	15.21	1.14	0.98	28.90	17.36	0.87
1200	19.16	27.16	7.23	13.67	1.16	0.99	28.61	17.49	0.94
1300	18.93	27.34	7.30	12.35	1.17	1.00	28.63	17.43	0.99
1400	18.70	27.50	7.41	11.34	1.18	1.00	28.35	17.19	1.02
1500	18.48	27.61	7.58	10.57	1.19	0.99	28.05	17.21	1.00
1600	18.27	27.75	7.76	9.90	1.20	0.99	28.05	17.07	1.08
1700	18.04	27.84	7.86	9.32	1.20	0.99	27.57	16.96	1.07
1800	17.76	27.94	7.79	8.91	1.21	0.99	27.67	16.72	1.09
1900	17.42	28.14	7.46	8.55	1.22	1.01	27.52	16.61	1.17
2000	17.01	28.39	6.89	8.33	1.23	1.04	27.19	16.55	1.21
2100	16.54	28.63	6.12	8.18	1.22	1.09	27.07	16.43	1.34
2200	15.98	28.99	5.32	8.06	1.23	1.14	26.69	16.32	1.46
2300	15.31	29.39	4.54	7.97	1.24	1.19	26.60	16.05	1.61
2400	14.59	29.89	3.83	7.91	1.26	1.24	26.22	15.86	1.79
2500	13.82	30.43	3.22	7.87	1.28	1.30	26.49	15.79	2.05

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.25V, Id = 149.96mA @ Temperature = -45°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	23.56	26.43	10.50	14.93	1.02	0.47	42.56	22.09	0.90
30	23.21	25.95	11.69	14.88	1.02	0.45	45.29	23.23	0.83
40	22.97	25.73	12.29	14.27	1.02	0.44	49.74	23.98	0.80
50	22.82	25.60	12.59	13.93	1.02	0.43	43.58	24.38	0.77
60	22.74	25.54	12.99	13.81	1.03	0.43	44.36	24.33	0.80
70	22.68	25.49	13.17	13.73	1.03	0.42	44.54	24.28	0.76
80	22.64	25.46	13.31	13.68	1.03	0.42	43.20	24.39	0.74
90	22.61	25.44	13.43	13.69	1.03	0.42	44.73	24.50	0.76
100	22.59	25.43	13.54	13.69	1.03	0.42	43.55	24.32	0.74
150	22.52	25.40	13.75	13.84	1.04	0.43	44.13	24.48	0.78
200	22.47	25.43	13.61	13.83	1.04	0.44	43.20	24.63	0.71
250	22.41	25.49	13.19	13.72	1.04	0.45	43.50	24.74	0.73
300	22.35	25.55	12.78	13.63	1.05	0.47	42.87	24.65	0.76
350	22.29	25.62	12.50	13.71	1.05	0.48	42.07	24.71	0.74
400	22.24	25.70	12.28	13.92	1.05	0.50	41.92	24.60	0.82
450	22.18	25.77	12.09	14.27	1.06	0.52	42.16	24.64	0.79
500	22.13	25.86	11.89	14.63	1.06	0.54	41.41	24.50	0.79
550	22.07	25.95	11.69	15.05	1.07	0.57	40.19	24.40	0.81
600	22.01	26.06	11.50	15.42	1.08	0.59	40.27	24.62	1.05
650	21.95	26.17	11.32	15.79	1.08	0.61	39.65	24.30	0.92
700	21.88	26.29	11.15	16.02	1.09	0.64	39.89	24.57	0.83
750	21.80	26.43	10.96	16.13	1.10	0.66	39.67	24.56	0.90
800	21.71	26.58	10.76	16.04	1.11	0.68	39.50	24.51	0.83
850	21.63	26.74	10.56	15.95	1.12	0.70	38.57	24.10	0.91
900	21.57	26.88	10.41	15.84	1.13	0.72	38.48	24.13	0.88
950	21.51	27.02	10.32	15.73	1.14	0.73	39.30	24.69	0.88
1000	21.44	27.17	10.26	15.56	1.15	0.75	39.28	24.69	0.93
1100	21.30	27.50	10.15	14.95	1.18	0.78	38.12	24.03	0.85
1200	21.15	27.86	10.04	14.12	1.21	0.80	38.36	24.34	0.94
1300	21.01	28.22	10.12	13.32	1.24	0.82	38.11	24.37	0.97
1400	20.86	28.60	10.27	12.52	1.28	0.84	36.94	23.79	0.98
1500	20.71	28.97	10.46	11.75	1.32	0.85	37.44	23.94	1.01
1600	20.57	29.38	10.69	11.07	1.36	0.86	37.18	23.89	1.07
1700	20.42	29.77	10.87	10.49	1.39	0.87	36.85	23.89	1.05
1800	20.24	30.18	10.86	9.97	1.43	0.89	36.36	23.68	1.08
1900	20.02	30.64	10.48	9.52	1.47	0.91	36.15	23.66	1.13
2000	19.74	31.13	9.62	9.10	1.51	0.94	36.51	23.85	1.19
2100	19.42	31.64	8.52	8.73	1.54	0.98	36.66	23.80	1.31
2200	19.02	32.19	7.41	8.38	1.57	1.02	37.06	23.99	1.44
2300	18.55	32.70	6.33	8.06	1.58	1.07	35.61	23.31	1.61
2400	18.01	33.31	5.39	7.68	1.60	1.11	34.90	23.00	1.70
2500	17.40	33.88	4.56	7.32	1.60	1.15	35.51	23.31	1.92

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 3.00V, Id = 72.10mA @ Temperature = +105°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	22.24	26.09	10.68	15.06	1.05	0.59	31.62	14.90	1.31
30	21.96	25.53	12.41	15.73	1.05	0.56	33.01	16.35	1.28
40	21.75	25.26	13.47	15.25	1.05	0.54	34.01	17.39	1.26
50	21.61	25.11	13.97	14.89	1.05	0.53	33.68	17.83	1.22
60	21.54	25.04	14.57	14.68	1.05	0.52	33.93	18.01	1.30
70	21.48	24.99	14.80	14.50	1.05	0.52	34.04	18.08	1.22
80	21.43	24.96	14.87	14.36	1.06	0.52	33.56	18.21	1.25
90	21.40	24.95	14.89	14.26	1.06	0.52	33.71	18.29	1.35
100	21.37	24.94	14.85	14.17	1.06	0.52	33.71	18.23	1.27
150	21.26	24.95	14.19	14.02	1.06	0.53	33.71	18.38	1.25
200	21.16	25.00	13.40	14.22	1.06	0.56	33.93	18.46	1.22
250	21.08	25.08	12.63	14.74	1.07	0.59	33.95	18.52	1.24
300	20.98	25.16	11.96	15.52	1.07	0.62	34.11	18.49	1.25
350	20.89	25.25	11.35	16.51	1.07	0.65	33.90	18.53	1.26
400	20.78	25.35	10.77	17.61	1.08	0.69	33.59	18.45	1.31
450	20.67	25.47	10.21	18.92	1.09	0.73	33.33	18.46	1.29
500	20.55	25.60	9.69	20.34	1.09	0.76	32.98	18.34	1.35
550	20.42	25.74	9.21	22.08	1.10	0.80	32.88	18.27	1.36
600	20.28	25.88	8.79	24.06	1.10	0.83	32.35	18.40	1.54
650	20.14	26.04	8.41	26.43	1.11	0.87	32.07	18.15	1.51
700	19.99	26.20	8.09	28.33	1.12	0.90	31.82	18.30	1.37
750	19.85	26.36	7.82	28.27	1.13	0.93	31.60	18.26	1.41
800	19.70	26.52	7.58	25.93	1.14	0.95	31.49	18.23	1.43
850	19.57	26.66	7.37	23.52	1.15	0.98	31.10	17.95	1.51
900	19.43	26.81	7.19	21.38	1.15	1.00	30.98	17.97	1.49
950	19.31	26.94	7.06	19.65	1.16	1.01	30.92	18.27	1.51
1000	19.17	27.06	6.94	18.21	1.17	1.03	30.68	18.23	1.58
1100	18.92	27.29	6.81	15.91	1.18	1.05	30.56	17.87	1.51
1200	18.68	27.48	6.79	14.20	1.20	1.05	30.27	18.01	1.60
1300	18.44	27.64	6.85	12.88	1.21	1.06	30.27	18.03	1.62
1400	18.21	27.76	6.96	11.79	1.22	1.05	30.02	17.74	1.69
1500	17.98	27.87	7.11	10.91	1.24	1.05	29.77	17.76	1.72
1600	17.73	28.01	7.21	10.19	1.25	1.04	29.71	17.67	1.79
1700	17.46	28.12	7.22	9.59	1.26	1.04	29.31	17.59	1.80
1800	17.13	28.27	7.07	9.12	1.27	1.05	29.42	17.41	1.84
1900	16.74	28.49	6.74	8.74	1.29	1.07	29.37	17.36	1.98
2000	16.29	28.75	6.22	8.44	1.31	1.09	28.96	17.29	2.06
2100	15.76	29.05	5.58	8.21	1.32	1.13	28.89	17.22	2.24
2200	15.15	29.44	4.90	8.03	1.35	1.16	28.45	17.16	2.47
2300	14.46	29.86	4.25	7.92	1.38	1.21	28.44	16.88	2.67
2400	13.71	30.37	3.67	7.83	1.43	1.25	28.07	16.64	2.95
2500	12.90	30.93	3.16	7.76	1.49	1.29	28.25	16.65	3.26

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.00V, Id = 135.50mA @ Temperature = +105°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	22.92	26.68	10.84	13.92	1.05	0.56	37.12	20.33	1.36
30	22.61	26.14	12.13	13.97	1.04	0.53	37.74	21.50	1.32
40	22.40	25.89	12.84	13.45	1.04	0.51	38.23	22.23	1.27
50	22.24	25.80	13.25	13.11	1.05	0.51	38.67	22.55	1.22
60	22.17	25.68	13.49	12.92	1.05	0.50	39.41	22.69	1.33
70	22.11	25.64	13.60	12.76	1.05	0.49	39.45	22.71	1.28
80	22.06	25.61	13.61	12.64	1.05	0.49	38.93	22.84	1.28
90	22.03	25.60	13.61	12.55	1.05	0.49	39.08	22.90	1.38
100	22.00	25.59	13.58	12.47	1.05	0.49	39.18	22.84	1.30
150	21.90	25.59	13.16	12.30	1.06	0.50	39.47	22.96	1.23
200	21.82	25.63	12.75	12.40	1.06	0.51	39.29	23.07	1.27
250	21.76	25.68	12.38	12.74	1.07	0.54	39.68	23.16	1.29
300	21.71	25.73	12.06	13.24	1.07	0.56	39.18	23.18	1.27
350	21.65	25.80	11.79	13.86	1.07	0.59	39.54	23.24	1.34
400	21.58	25.88	11.46	14.51	1.08	0.61	39.37	23.19	1.32
450	21.51	25.97	11.11	15.23	1.09	0.64	39.33	23.23	1.32
500	21.43	26.07	10.75	15.92	1.09	0.67	39.01	23.15	1.39
550	21.34	26.17	10.41	16.70	1.10	0.70	38.77	23.14	1.41
600	21.25	26.30	10.09	17.49	1.11	0.72	38.63	23.27	1.64
650	21.16	26.42	9.79	18.38	1.12	0.75	38.37	23.04	1.52
700	21.06	26.56	9.54	19.26	1.13	0.78	38.47	23.20	1.38
750	20.96	26.71	9.33	20.13	1.14	0.80	38.16	23.21	1.45
800	20.87	26.85	9.14	20.77	1.15	0.83	37.98	23.17	1.47
850	20.78	26.99	8.96	21.15	1.16	0.85	37.53	22.87	1.55
900	20.69	27.13	8.81	21.01	1.17	0.87	37.45	22.91	1.50
950	20.61	27.27	8.69	20.50	1.18	0.89	37.52	23.24	1.53
1000	20.52	27.41	8.59	19.73	1.19	0.90	37.37	23.10	1.57
1100	20.34	27.70	8.48	17.86	1.22	0.92	36.78	22.73	1.52
1200	20.17	27.98	8.47	16.13	1.24	0.94	36.55	22.85	1.58
1300	20.00	28.25	8.55	14.69	1.27	0.95	36.43	22.88	1.63
1400	19.84	28.51	8.70	13.45	1.30	0.95	36.12	22.47	1.67
1500	19.67	28.74	8.89	12.44	1.32	0.96	35.86	22.46	1.70
1600	19.49	29.00	9.05	11.58	1.35	0.96	35.71	22.41	1.79
1700	19.28	29.24	9.09	10.87	1.37	0.97	35.25	22.33	1.77
1800	19.03	29.50	8.92	10.27	1.39	0.98	35.45	22.24	1.83
1900	18.73	29.81	8.52	9.78	1.42	1.00	35.29	22.23	1.95
2000	18.37	30.14	7.84	9.36	1.44	1.03	35.09	22.19	2.04
2100	17.94	30.49	6.99	9.00	1.45	1.06	35.05	22.10	2.20
2200	17.43	30.91	6.10	8.70	1.47	1.11	34.76	22.07	2.38
2300	16.83	31.33	5.24	8.48	1.49	1.16	34.51	21.70	2.60
2400	16.18	31.85	4.47	8.26	1.51	1.20	34.04	21.40	2.84
2500	15.44	32.33	3.81	8.08	1.54	1.25	34.35	21.57	3.12

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 2.70V, Id = 64.27mA @ Temperature = +105°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	21.94	25.86	10.58	15.46	1.05	0.60	29.54	13.97	1.33
30	21.69	25.28	12.49	16.65	1.05	0.57	31.79	15.43	1.29
40	21.51	25.01	13.71	16.32	1.05	0.55	32.84	16.53	1.26
50	21.38	24.86	14.41	16.02	1.05	0.54	32.79	17.00	1.22
60	21.32	24.79	15.08	15.82	1.05	0.53	32.66	17.15	1.27
70	21.26	24.75	15.38	15.64	1.06	0.53	32.74	17.24	1.27
80	21.22	24.72	15.53	15.50	1.06	0.53	32.57	17.36	1.23
90	21.19	24.70	15.54	15.41	1.06	0.53	32.43	17.46	1.23
100	21.16	24.69	15.50	15.31	1.06	0.53	32.61	17.36	1.25
150	21.06	24.70	14.76	15.16	1.06	0.54	32.64	17.51	1.28
200	20.96	24.76	13.82	15.41	1.06	0.57	32.67	17.59	1.23
250	20.87	24.84	12.88	16.06	1.07	0.60	32.83	17.65	1.23
300	20.77	24.93	12.09	17.01	1.07	0.63	32.85	17.59	1.29
350	20.67	25.03	11.39	18.28	1.07	0.67	32.28	17.62	1.26
400	20.56	25.15	10.73	19.75	1.08	0.71	32.25	17.53	1.30
450	20.44	25.27	10.10	21.50	1.08	0.74	31.83	17.53	1.31
500	20.31	25.41	9.53	23.43	1.09	0.78	31.35	17.40	1.33
550	20.17	25.56	9.03	25.74	1.10	0.82	31.12	17.30	1.35
600	20.03	25.72	8.58	27.90	1.10	0.85	30.73	17.43	1.60
650	19.87	25.88	8.17	28.73	1.11	0.89	30.38	17.17	1.46
700	19.72	26.05	7.83	26.99	1.12	0.92	30.11	17.33	1.42
750	19.56	26.22	7.55	24.45	1.13	0.95	30.01	17.29	1.48
800	19.41	26.38	7.30	22.04	1.13	0.97	29.88	17.26	1.41
850	19.27	26.53	7.08	20.11	1.14	0.99	29.47	16.95	1.51
900	19.13	26.66	6.91	18.50	1.15	1.01	29.45	16.97	1.47
950	18.99	26.78	6.78	17.16	1.15	1.02	29.42	17.31	1.49
1000	18.85	26.90	6.67	16.05	1.16	1.04	29.29	17.29	1.55
1100	18.59	27.10	6.58	14.21	1.17	1.05	29.08	16.91	1.49
1200	18.35	27.26	6.60	12.81	1.18	1.05	28.81	17.09	1.56
1300	18.11	27.37	6.70	11.70	1.19	1.05	28.93	17.08	1.64
1400	17.89	27.46	6.87	10.79	1.20	1.04	28.64	16.79	1.67
1500	17.66	27.53	7.09	10.05	1.21	1.03	28.38	16.84	1.69
1600	17.41	27.64	7.26	9.44	1.22	1.02	28.37	16.73	1.78
1700	17.14	27.73	7.30	8.93	1.23	1.02	28.01	16.66	1.77
1800	16.80	27.83	7.15	8.58	1.24	1.03	28.10	16.45	1.83
1900	16.40	28.05	6.79	8.26	1.25	1.05	28.04	16.39	1.94
2000	15.92	28.33	6.24	8.06	1.28	1.08	27.70	16.37	2.07
2100	15.36	28.63	5.54	7.90	1.29	1.12	27.59	16.28	2.22
2200	14.71	29.04	4.82	7.79	1.32	1.16	27.20	16.23	2.47
2300	13.97	29.49	4.15	7.74	1.36	1.21	27.15	15.92	2.69
2400	13.19	30.03	3.54	7.70	1.41	1.26	26.77	15.71	2.96
2500	12.33	30.62	3.05	7.65	1.48	1.30	26.97	15.69	3.30

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.25V, Id = 142.71mA @ Temperature = +105°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
20	22.78	26.89	10.63	12.99	1.06	0.58	36.35	20.37	1.37
30	22.50	26.32	12.00	13.26	1.05	0.55	37.94	21.64	1.32
40	22.30	26.05	12.74	12.88	1.05	0.53	39.39	22.41	1.30
50	22.16	25.92	13.19	12.62	1.05	0.52	38.87	22.73	1.25
60	22.09	25.83	13.44	12.47	1.06	0.51	38.63	22.90	1.34
70	22.03	25.78	13.55	12.33	1.06	0.51	39.39	22.95	1.28
80	21.99	25.75	13.59	12.23	1.06	0.51	39.07	23.09	1.29
90	21.96	25.73	13.56	12.16	1.06	0.50	39.07	23.16	1.36
100	21.93	25.71	13.53	12.08	1.06	0.50	39.26	23.12	1.33
150	21.84	25.71	13.06	11.94	1.06	0.51	39.20	23.27	1.33
200	21.78	25.74	12.60	12.03	1.07	0.52	39.71	23.39	1.29
250	21.73	25.78	12.21	12.35	1.07	0.54	39.72	23.51	1.32
300	21.68	25.82	11.88	12.81	1.07	0.56	40.03	23.54	1.29
350	21.64	25.88	11.61	13.38	1.08	0.59	39.49	23.63	1.32
400	21.58	25.95	11.31	13.96	1.08	0.61	39.83	23.60	1.35
450	21.52	26.02	10.98	14.60	1.09	0.64	39.81	23.65	1.40
500	21.45	26.12	10.65	15.20	1.09	0.66	39.04	23.59	1.41
550	21.38	26.22	10.34	15.86	1.10	0.69	39.34	23.59	1.44
600	21.30	26.33	10.06	16.52	1.11	0.71	39.25	23.71	1.76
650	21.22	26.45	9.80	17.24	1.12	0.74	39.12	23.49	1.52
700	21.13	26.58	9.57	17.93	1.13	0.76	38.88	23.65	1.47
750	21.05	26.71	9.38	18.62	1.14	0.79	38.79	23.67	1.49
800	20.96	26.85	9.23	19.12	1.15	0.81	38.81	23.64	1.50
850	20.88	26.99	9.06	19.47	1.16	0.83	38.19	23.34	1.58
900	20.80	27.12	8.93	19.44	1.17	0.85	37.90	23.38	1.51
950	20.73	27.27	8.83	19.15	1.18	0.86	38.11	23.70	1.51
1000	20.64	27.41	8.74	18.62	1.19	0.88	37.87	23.53	1.62
1100	20.48	27.71	8.65	17.16	1.22	0.90	37.36	23.17	1.54
1200	20.32	28.01	8.64	15.68	1.24	0.92	37.10	23.24	1.63
1300	20.15	28.30	8.73	14.39	1.27	0.93	37.01	23.30	1.64
1400	19.99	28.58	8.87	13.24	1.30	0.94	36.46	22.90	1.69
1500	19.82	28.84	9.08	12.29	1.33	0.94	36.25	22.86	1.70
1600	19.64	29.14	9.24	11.47	1.36	0.95	36.30	22.81	1.79
1700	19.44	29.41	9.28	10.78	1.39	0.95	35.83	22.69	1.80
1800	19.19	29.69	9.10	10.20	1.41	0.97	35.83	22.65	1.84
1900	18.90	30.04	8.68	9.71	1.44	0.99	35.91	22.65	1.98
2000	18.54	30.40	7.99	9.29	1.46	1.02	35.65	22.59	2.03
2100	18.12	30.77	7.12	8.92	1.48	1.05	35.52	22.48	2.22
2200	17.62	31.20	6.21	8.60	1.50	1.10	35.37	22.47	2.44
2300	17.03	31.64	5.33	8.37	1.51	1.15	35.00	22.08	2.65
2400	16.38	32.16	4.54	8.15	1.54	1.19	34.52	21.74	2.86
2500	15.64	32.65	3.87	7.94	1.57	1.24	34.89	21.92	3.17