

Typical Performance Data

FREQ.	ATTENUATION	VSWR
(MHz)	(dB)	(:1)
10	7.00	1.07
20	7.00	1.07
50	7.00	1.07
100	7.01	1.07
200	7.03	1.07
300	7.04	1.07
400	7.05	1.07
500	7.06	1.07
600	7.06	1.07
700	7.07	1.07
800	7.08	1.07
900	7.09	1.07
1000	7.09	1.07
1100	7.10	1.07
1200	7.11	1.07
1300	7.11	1.07
1400	7.12	1.08
1500	7.13	1.08
1600	7.13	1.08
1700	7.14	1.08
1800	7.14	1.08
1900	7.15	1.09
2000	7.16	1.09
2100	7.16	1.09
2200	7.17	1.09
2300	7.18	1.10
2400	7.18	1.10
2500	7.19	1.10
2600	7.20	1.11
2700	7.20	1.11
2800	7.21	1.11
2900	7.22	1.12
3000	7.22	1.12
3100	7.23	1.13
3200	7.23	1.13
3300	7.24	1.13
3400	7.25	1.14
3500	7.25	1.14
3600	7.26	1.14
3700	7.27	1.15
3800	7.27	1.15
3900	7.28	1.15
4000	7.29	1.16
4100	7.29	1.16
4200	7.30	1.16
4300	7.30	1.16
4400	7.31	1.16
4500	7.32	1.16
4600	7.32	1.17
4700	7.33	1.17
4800	7.34	1.17
4900	7.34	1.17
5000	7.35	1.17
5100	7.35	1.17
5200	7.36	1.17
5300	7.36	1.17
5400	7.37	1.17
5500	7.38	1.17
5800	7.40	1.17
6000	7.41	1.17