

Typical Performance Data

FREQ.	ATTENUATION	VSWR
(MHz)	(dB)	(:1)
10	8.95	1.11
20	8.95	1.11
50	8.96	1.11
100	8.97	1.11
200	8.98	1.11
300	9.00	1.11
400	9.01	1.11
500	9.02	1.11
600	9.03	1.11
700	9.04	1.11
800	9.05	1.11
900	9.07	1.11
1000	9.07	1.12
1100	9.08	1.12
1200	9.09	1.12
1300	9.10	1.12
1400	9.11	1.12
1500	9.11	1.12
1600	9.12	1.12
1700	9.13	1.13
1800	9.13	1.13
1900	9.14	1.13
2000	9.15	1.13
2100	9.15	1.13
2200	9.16	1.14
2300	9.17	1.14
2400	9.18	1.14
2500	9.18	1.14
2600	9.19	1.14
2700	9.19	1.15
2800	9.20	1.15
2900	9.21	1.15
3000	9.21	1.15
3100	9.22	1.16
3200	9.23	1.16
3300	9.23	1.16
3400	9.24	1.16
3500	9.25	1.16
3600	9.25	1.17
3700	9.26	1.17
3800	9.27	1.17
3900	9.28	1.17
4000	9.28	1.18
4100	9.29	1.18
4200	9.29	1.18
4300	9.30	1.18
4400	9.31	1.18
4500	9.32	1.18
4600	9.32	1.18
4700	9.33	1.19
4800	9.33	1.19
4900	9.34	1.19
5000	9.35	1.19
5100	9.35	1.19
5200	9.36	1.19
5300	9.37	1.19
5400	9.37	1.19
5500	9.38	1.19
5800	9.40	1.19
6000	9.42	1.19