

Waveguide WR10 UG387/U to 1.0mm-F**WR10-10+***Typical Performance Data (+25°C)*

FREQ.	INSERTION LOSS	1.0mm-FEMALE VSWR
(GHz)	(dB)	(:1)
75	0.45	1.11
76	0.44	1.13
77	0.45	1.15
78	0.44	1.17
79	0.44	1.18
80	0.42	1.20
81	0.43	1.27
82	0.50	1.37
83	0.56	1.46
84	0.61	1.51
85	0.62	1.51
86	0.62	1.47
87	0.57	1.39
88	0.57	1.33
89	0.56	1.30
90	0.55	1.28
91	0.54	1.23
92	0.53	1.16
93	0.55	1.14
94	0.58	1.20
95	0.61	1.27
96	0.63	1.31
97	0.66	1.32
98	0.70	1.38
99	0.75	1.50
100	0.84	1.65
101	0.87	1.72
102	0.87	1.72
103	0.85	1.68
104	0.85	1.68
105	0.88	1.73
106	0.89	1.78
107	0.89	1.77
108	0.81	1.62
109	0.71	1.43
110	0.64	1.28



P.O. Box 350166, Brooklyn, New York 11235-0003 • Fax (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
 The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
 WR10-10+
 2/11/2026
 Page 1 of 1