

Fixed Attenuator**WR22-ATT-30+***Typical Performance Data (+25°C)*

FREQ.	ATTENUATION	WR22 INPUT VSWR	WR22 OUTPUT VSWR
(GHz)	(dB)	(:1)	(:1)
33.0	29.35	1.11	1.12
33.5	29.34	1.11	1.10
34.0	29.41	1.12	1.12
34.5	29.48	1.11	1.13
35.0	29.43	1.08	1.11
35.5	29.51	1.08	1.09
36.0	29.60	1.08	1.07
36.5	29.74	1.08	1.08
37.0	29.86	1.07	1.08
37.5	29.95	1.06	1.07
38.0	30.16	1.06	1.06
38.5	30.39	1.07	1.05
39.0	30.38	1.07	1.05
39.5	30.46	1.06	1.06
40.0	30.64	1.05	1.05
40.5	30.82	1.07	1.05
41.0	30.93	1.08	1.07
41.5	30.79	1.08	1.06
42.0	30.90	1.07	1.06
42.5	30.98	1.07	1.06
43.0	31.23	1.08	1.06
43.5	31.26	1.08	1.06
44.0	31.27	1.07	1.05
44.5	31.36	1.07	1.05
45.0	31.53	1.06	1.05
45.5	31.69	1.06	1.08
46.0	31.67	1.06	1.07
46.5	31.75	1.06	1.05
47.0	32.07	1.11	1.06
47.5	32.28	1.10	1.12
48.0	32.40	1.10	1.13
48.5	32.40	1.08	1.10
49.0	32.48	1.08	1.07
49.5	32.58	1.11	1.06
50.0	32.95	1.10	1.12



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
 The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS