

# Fixed Attenuator

# YAT-0+

## Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.001	0.02	1.02
0.002	0.02	1.01
0.004	0.02	1.01
0.006	0.02	1.01
0.008	0.02	1.01
0.010	0.02	1.01
0.020	0.02	1.01
0.040	0.02	1.01
0.060	0.02	1.02
0.080	0.02	1.02
0.100	0.02	1.02
0.200	0.03	1.03
0.400	0.03	1.06
0.600	0.03	1.08
0.800	0.04	1.10
1.000	0.04	1.11
1.200	0.04	1.12
1.400	0.04	1.13
1.600	0.04	1.12
1.800	0.05	1.11
2.000	0.05	1.10
2.200	0.05	1.09
2.400	0.05	1.07
2.600	0.05	1.06
2.800	0.05	1.05
3.000	0.05	1.04
3.200	0.05	1.04
3.400	0.04	1.03
3.600	0.03	1.03
3.800	0.03	1.03
4.000	0.03	1.03
4.200	0.02	1.02
4.400	0.02	1.02
4.600	0.02	1.04
4.800	0.02	1.06
5.000	0.03	1.08
5.200	0.04	1.12
5.400	0.06	1.16
5.600	0.08	1.20
5.800	0.10	1.24
6.000	0.12	1.29
7.000	0.21	1.44
8.000	0.16	1.33
9.000	0.10	1.12
10.000	0.10	1.08
11.000	0.10	1.10
12.000	0.09	1.10
13.000	0.08	1.11
14.000	0.15	1.22
15.000	0.24	1.32
16.000	0.28	1.33
17.000	0.30	1.34
18.000	0.33	1.61



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site  
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)



IF/RF MICROWAVE COMPONENTS

REV. OR  
YAT-0+  
2/26/2013  
Page 1 of 1