

Fixed Attenuator Die

YAT-0-D+

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	0.01	1.00
0.02	0.01	1.00
0.04	0.01	1.00
0.06	0.01	1.00
0.08	0.01	1.00
0.10	0.01	1.00
0.20	0.01	1.00
0.40	0.01	1.01
0.60	0.02	1.01
0.80	0.01	1.02
1.00	0.01	1.02
1.20	0.02	1.02
1.40	0.02	1.03
1.60	0.02	1.03
1.80	0.02	1.04
2.00	0.02	1.04
3.00	0.02	1.06
4.00	0.02	1.09
5.00	0.03	1.11
6.00	0.02	1.14
7.00	0.05	1.16
8.00	0.07	1.18
9.00	0.08	1.21
10.0	0.09	1.23
11.0	0.13	1.25
12.0	0.16	1.28
13.0	0.16	1.31
14.0	0.20	1.33
15.0	0.25	1.35
16.0	0.17	1.38
17.0	0.27	1.40
18.0	0.33	1.42
19.0	0.37	1.45
20.0	0.26	1.48
21.0	0.37	1.49
22.0	0.41	1.51
23.0	0.45	1.53
24.0	0.35	1.54
25.0	0.45	1.55
26.0	0.48	1.57
27.0	0.45	1.59
28.0	0.67	1.60
29.0	0.68	1.59
30.0	0.41	1.61
31.0	0.53	1.61
32.0	1.00	1.60
33.0	0.69	1.58
34.0	0.47	1.58
35.0	0.56	1.57
36.0	0.93	1.54
37.0	0.93	1.50
38.0	0.60	1.49
39.0	0.77	1.47
40.0	1.39	1.44



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
YAT-0-D+
6/29/2016
Page 1 of 1