

Fixed Attenuator

YAT-1+

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.001	1.00	1.02
0.002	1.01	1.01
0.004	1.01	1.01
0.006	1.01	1.01
0.008	1.01	1.01
0.010	1.01	1.01
0.020	1.01	1.01
0.040	1.01	1.01
0.060	1.01	1.01
0.080	1.01	1.02
0.100	1.02	1.02
0.200	1.02	1.03
0.400	1.02	1.04
0.600	1.03	1.06
0.800	1.03	1.07
1.000	1.03	1.07
1.200	1.03	1.08
1.400	1.03	1.07
1.600	1.04	1.07
1.800	1.04	1.06
2.000	1.04	1.04
2.200	1.05	1.03
2.400	1.05	1.03
2.600	1.05	1.04
2.800	1.05	1.05
3.000	1.05	1.06
3.200	1.05	1.08
3.400	1.05	1.09
3.600	1.05	1.09
3.800	1.04	1.09
4.000	1.04	1.09
4.200	1.04	1.09
4.400	1.03	1.08
4.600	1.03	1.07
4.800	1.03	1.09
5.000	1.05	1.12
5.200	1.06	1.16
5.400	1.09	1.21
5.600	1.11	1.25
5.800	1.14	1.30
6.000	1.18	1.36
7.000	1.32	1.54
8.000	1.29	1.47
9.000	1.23	1.29
10.000	1.20	1.17
11.000	1.19	1.15
12.000	1.23	1.24
13.000	1.26	1.29
14.000	1.32	1.29
15.000	1.37	1.31
16.000	1.42	1.30
17.000	1.42	1.24
18.000	1.40	1.36



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
YAT-1+
2/26/2013
Page 1 of 1