

Fixed Attenuator Die

YAT-1-D+

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	1.01	1.00
0.02	1.01	1.00
0.04	1.01	1.00
0.06	1.01	1.00
0.08	1.01	1.00
0.10	1.01	1.00
0.20	1.01	1.00
0.40	1.01	1.01
0.60	1.01	1.01
0.80	1.01	1.01
1.00	1.00	1.02
1.20	1.01	1.02
1.40	1.01	1.02
1.60	1.01	1.03
1.80	1.01	1.03
2.00	1.01	1.03
3.00	1.01	1.05
4.00	1.01	1.07
5.00	1.02	1.08
6.00	1.00	1.11
7.00	1.03	1.12
8.00	1.05	1.14
9.00	1.05	1.16
10.0	1.06	1.17
11.0	1.10	1.19
12.0	1.12	1.22
13.0	1.10	1.24
14.0	1.17	1.25
15.0	1.19	1.27
16.0	1.12	1.29
17.0	1.22	1.31
18.0	1.27	1.33
19.0	1.29	1.34
20.0	1.19	1.37
21.0	1.29	1.38
22.0	1.32	1.39
23.0	1.38	1.41
24.0	1.28	1.43
25.0	1.37	1.44
26.0	1.41	1.45
27.0	1.39	1.47
28.0	1.62	1.47
29.0	1.62	1.47
30.0	1.34	1.50



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site www.minicircuits.com



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS



REV. OR
YAT-1-D+
6/29/2016
Page 1 of 1