

Fixed Attenuator

YAT-10+

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.001	9.96	1.03
0.002	9.98	1.03
0.004	9.98	1.03
0.006	9.98	1.03
0.008	9.98	1.03
0.010	10.00	1.03
0.020	10.01	1.03
0.040	10.01	1.02
0.060	10.00	1.02
0.080	10.00	1.02
0.100	10.00	1.02
0.200	10.01	1.03
0.400	10.01	1.03
0.600	10.02	1.04
0.800	10.02	1.04
1.000	10.02	1.05
1.200	10.02	1.05
1.400	10.03	1.05
1.600	10.03	1.05
1.800	10.04	1.05
2.000	10.05	1.05
2.200	10.05	1.05
2.400	10.06	1.05
2.600	10.06	1.05
2.800	10.07	1.04
3.000	10.07	1.04
3.200	10.06	1.05
3.400	10.06	1.04
3.600	10.06	1.05
3.800	10.06	1.05
4.000	10.06	1.07
4.200	10.06	1.09
4.400	10.06	1.10
4.600	10.06	1.12
4.800	10.07	1.14
5.000	10.09	1.17
5.200	10.10	1.20
5.400	10.12	1.22
5.600	10.14	1.26
5.800	10.17	1.28
6.000	10.19	1.31
7.000	10.32	1.43
8.000	10.40	1.48
9.000	10.44	1.45
10.000	10.47	1.38
11.000	10.46	1.35
12.000	10.49	1.35
13.000	10.51	1.36
14.000	10.53	1.33
15.000	10.54	1.31
16.000	10.62	1.36
17.000	10.84	1.53
18.000	11.04	1.74



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
YAT-10+
2/26/2013
Page 1 of 1