

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	12.00	1.08
0.02	12.01	1.08
0.04	12.00	1.08
0.06	12.00	1.08
0.08	12.00	1.08
0.10	12.00	1.08
0.20	12.00	1.08
0.40	12.00	1.08
0.60	12.00	1.08
0.80	12.00	1.08
1.00	12.00	1.08
1.20	11.99	1.08
1.40	12.00	1.08
1.60	12.00	1.09
1.80	12.00	1.09
2.00	12.00	1.09
3.00	12.00	1.09
4.00	11.99	1.09
5.00	11.98	1.10
6.00	12.01	1.10
7.00	12.00	1.11
8.00	12.01	1.12
9.00	12.01	1.13
10.0	12.02	1.13
11.0	12.02	1.14
12.0	12.05	1.15
13.0	12.14	1.16
14.0	12.11	1.17
15.0	12.15	1.18
16.0	12.15	1.19
17.0	12.19	1.20
18.0	12.23	1.20
19.0	12.22	1.19
20.0	12.13	1.19
21.0	12.18	1.22
22.0	12.14	1.25
23.0	12.16	1.28
24.0	12.38	1.28
25.0	12.30	1.28
26.0	12.34	1.29
27.0	12.38	1.31
28.0	12.52	1.31
29.0	12.52	1.32
30.0	12.50	1.34
31.0	12.52	1.35
32.0	12.56	1.36
33.0	12.60	1.35
34.0	12.73	1.39
35.0	12.85	1.38
36.0	12.81	1.40
37.0	13.00	1.41
38.0	12.99	1.45
39.0	13.05	1.43
40.0	13.59	1.48