

Fixed Attenuator Die

YAT-2-D+

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	1.99	1.01
0.02	1.99	1.01
0.04	1.99	1.01
0.06	1.99	1.01
0.08	1.99	1.01
0.10	2.00	1.01
0.20	1.99	1.01
0.40	1.99	1.01
0.60	1.99	1.02
0.80	1.99	1.02
1.00	1.99	1.02
1.20	1.99	1.03
1.40	2.00	1.03
1.60	2.00	1.04
1.80	2.00	1.04
2.00	2.00	1.05
3.00	2.00	1.07
4.00	2.00	1.10
5.00	2.02	1.12
6.00	2.00	1.15
7.00	2.03	1.17
8.00	2.06	1.20
9.00	2.07	1.22
10.0	2.09	1.25
11.0	2.13	1.27
12.0	2.16	1.30
13.0	2.17	1.33
14.0	2.25	1.35
15.0	2.24	1.38
16.0	2.22	1.40
17.0	2.32	1.43
18.0	2.37	1.45
19.0	2.40	1.47
20.0	2.36	1.51
21.0	2.44	1.52
22.0	2.46	1.54
23.0	2.55	1.57
24.0	2.50	1.59
25.0	2.55	1.60
26.0	2.60	1.61
27.0	2.60	1.64
28.0	2.82	1.65
29.0	2.79	1.65
30.0	2.60	1.68
31.0	2.71	1.67
32.0	3.11	1.66
33.0	2.83	1.66
34.0	2.75	1.67
35.0	2.86	1.66
36.0	3.09	1.65
37.0	3.07	1.65
38.0	2.83	1.64
39.0	2.98	1.64
40.0	3.40	1.62



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
YAT-2-D+
6/29/2016
Page 1 of 1