

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	29.98	1.02
0.02	29.97	1.03
0.04	29.97	1.03
0.06	29.97	1.03
0.08	29.97	1.03
0.10	29.97	1.03
0.20	29.98	1.03
0.40	29.98	1.03
0.60	29.98	1.03
0.80	29.99	1.04
1.00	29.98	1.04
1.20	29.99	1.05
1.40	29.99	1.05
1.60	30.00	1.05
1.80	29.99	1.05
2.00	30.00	1.05
2.20	29.99	1.05
2.40	29.99	1.04
2.60	30.00	1.04
2.80	30.00	1.03
3.00	30.00	1.03
3.20	30.00	1.03
3.40	30.00	1.04
3.60	30.01	1.05
3.80	30.02	1.07
4.00	30.04	1.09
4.20	30.04	1.11
4.40	30.07	1.13
4.60	30.10	1.15
4.80	30.12	1.18
5.00	30.15	1.20
5.20	30.19	1.23
5.40	30.22	1.25
5.60	30.26	1.27
5.80	30.28	1.30
6.00	30.31	1.32
7.00	30.41	1.39
8.00	30.48	1.39
9.00	30.48	1.32
10.00	30.36	1.29
11.00	30.38	1.39
12.00	30.52	1.54
13.00	30.51	1.64
14.00	30.48	1.61
15.00	30.62	1.47
16.00	30.72	1.34
17.00	30.99	1.37
18.00	31.46	1.57