

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	30.10	1.03
0.02	30.06	1.03
0.04	30.04	1.03
0.06	30.08	1.03
0.08	30.06	1.03
0.10	30.05	1.03
0.20	30.06	1.03
0.40	30.05	1.03
0.60	30.06	1.03
0.80	30.06	1.03
1.00	30.06	1.03
1.20	30.05	1.03
1.40	30.05	1.03
1.60	30.05	1.03
1.80	30.05	1.03
2.00	30.05	1.03
3.00	30.04	1.03
4.00	30.03	1.04
5.00	30.03	1.04
6.00	29.96	1.06
7.00	29.98	1.06
8.00	29.98	1.07
9.00	29.99	1.07
10.0	29.94	1.08
11.0	29.94	1.08
12.0	30.05	1.08
13.0	30.01	1.09
14.0	30.04	1.11
15.0	29.88	1.13
16.0	29.93	1.13
17.0	29.99	1.13
18.0	29.91	1.14
19.0	29.97	1.15
20.0	29.99	1.17
21.0	29.95	1.17
22.0	29.89	1.18
23.0	29.98	1.20
24.0	29.98	1.21
25.0	29.98	1.22
26.0	29.98	1.24
27.0	30.18	1.25
28.0	30.63	1.26
29.0	30.23	1.27
30.0	29.99	1.30
31.0	30.26	1.30
32.0	30.88	1.32
33.0	30.29	1.33
34.0	30.23	1.35
35.0	30.36	1.38
36.0	30.85	1.39
37.0	30.95	1.42
38.0	30.86	1.44
39.0	31.62	1.47
40.0	32.64	1.50