

*Typical Performance Data*

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	4.02	1.01
0.02	4.02	1.01
0.04	4.02	1.01
0.06	4.02	1.01
0.08	4.02	1.01
0.10	4.02	1.01
0.20	4.03	1.02
0.40	4.03	1.02
0.60	4.03	1.03
0.80	4.03	1.03
1.00	4.04	1.04
1.20	4.04	1.04
1.40	4.04	1.04
1.60	4.04	1.04
1.80	4.04	1.04
2.00	4.04	1.03
2.20	4.04	1.03
2.40	4.04	1.03
2.60	4.03	1.03
2.80	4.03	1.02
3.00	4.03	1.02
3.20	4.03	1.02
3.40	4.02	1.03
3.60	4.02	1.03
3.80	4.02	1.04
4.00	4.02	1.05
4.20	4.03	1.06
4.40	4.03	1.08
4.60	4.04	1.10
4.80	4.05	1.12
5.00	4.06	1.14
5.20	4.07	1.16
5.40	4.09	1.18
5.60	4.10	1.20
5.80	4.11	1.21
6.00	4.12	1.23
7.00	4.16	1.28
8.00	4.17	1.26
9.00	4.20	1.23
10.00	4.26	1.23
11.00	4.31	1.27
12.00	4.35	1.30
13.00	4.37	1.29
14.00	4.41	1.29
15.00	4.40	1.32
16.00	4.37	1.34
17.00	4.45	1.35
18.00	4.54	1.36