

# Fixed Attenuator

# YAT-5+

## Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	5.02	1.00
0.02	5.02	1.00
0.04	5.02	1.00
0.06	5.02	1.01
0.08	5.02	1.01
0.10	5.02	1.01
0.20	5.03	1.01
0.40	5.04	1.02
0.60	5.05	1.03
0.80	5.05	1.04
1.00	5.06	1.04
1.20	5.06	1.04
1.40	5.06	1.04
1.60	5.07	1.03
1.80	5.07	1.03
2.00	5.07	1.03
2.20	5.07	1.02
2.40	5.07	1.02
2.60	5.07	1.01
2.80	5.07	1.01
3.00	5.07	1.01
3.20	5.08	1.01
3.40	5.08	1.01
3.60	5.08	1.02
3.80	5.09	1.03
4.00	5.10	1.04
4.20	5.10	1.05
4.40	5.11	1.07
4.60	5.12	1.08
4.80	5.13	1.11
5.00	5.14	1.13
5.20	5.15	1.15
5.40	5.17	1.17
5.60	5.18	1.19
5.80	5.19	1.20
6.00	5.21	1.22
7.00	5.25	1.27
8.00	5.27	1.26
9.00	5.34	1.23
10.00	5.50	1.26
11.00	5.69	1.40
12.00	5.80	1.49
13.00	5.80	1.49
14.00	5.73	1.49
15.00	5.60	1.49
16.00	5.50	1.45
17.00	5.51	1.31
18.00	5.50	1.22



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site  
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)



IF/RF MICROWAVE COMPONENTS

REV. OR  
YAT-5+  
2/13/2013  
Page 1 of 1