

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.001	5.98	1.01
0.002	5.99	1.01
0.004	6.00	1.01
0.006	6.00	1.01
0.008	6.00	1.01
0.010	6.01	1.01
0.020	6.02	1.01
0.040	6.02	1.02
0.060	6.01	1.02
0.080	6.01	1.02
0.100	6.01	1.02
0.200	6.02	1.02
0.400	6.02	1.04
0.600	6.03	1.05
0.800	6.03	1.05
1.000	6.03	1.06
1.200	6.03	1.07
1.400	6.04	1.07
1.600	6.04	1.07
1.800	6.04	1.07
2.000	6.05	1.07
2.200	6.06	1.06
2.400	6.06	1.06
2.600	6.06	1.06
2.800	6.07	1.05
3.000	6.07	1.06
3.200	6.06	1.05
3.400	6.06	1.05
3.600	6.06	1.05
3.800	6.05	1.06
4.000	6.05	1.06
4.200	6.04	1.06
4.400	6.04	1.07
4.600	6.04	1.08
4.800	6.05	1.09
5.000	6.06	1.12
5.200	6.07	1.14
5.400	6.09	1.17
5.600	6.11	1.21
5.800	6.13	1.24
6.000	6.16	1.27
7.000	6.27	1.39
8.000	6.33	1.42
9.000	6.36	1.37
10.000	6.37	1.31
11.000	6.37	1.30
12.000	6.43	1.36
13.000	6.52	1.40
14.000	6.59	1.37
15.000	6.63	1.33
16.000	6.70	1.28
17.000	6.78	1.28
18.000	6.83	1.41