

Fixed Attenuator Die

YAT-6-D+

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	5.99	1.01
0.02	5.99	1.01
0.04	5.98	1.01
0.06	5.98	1.01
0.08	5.98	1.01
0.10	5.98	1.01
0.20	5.98	1.01
0.40	5.99	1.01
0.60	5.99	1.02
0.80	5.99	1.02
1.00	5.99	1.02
1.20	5.98	1.03
1.40	5.99	1.03
1.60	5.98	1.03
1.80	5.99	1.04
2.00	5.99	1.04
3.00	5.99	1.06
4.00	5.99	1.08
5.00	5.99	1.10
6.00	6.02	1.12
7.00	6.03	1.14
8.00	6.06	1.16
9.00	6.06	1.18
10.0	6.09	1.20
11.0	6.10	1.22
12.0	6.14	1.24
13.0	6.22	1.26
14.0	6.18	1.28
15.0	6.20	1.31
16.0	6.23	1.33
17.0	6.29	1.35
18.0	6.37	1.35
19.0	6.43	1.37
20.0	6.43	1.40
21.0	6.50	1.43
22.0	6.44	1.44
23.0	6.48	1.45
24.0	6.68	1.47
25.0	6.63	1.49
26.0	6.70	1.50
27.0	6.75	1.51
28.0	6.87	1.53
29.0	6.90	1.54
30.0	6.88	1.54



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site www.minicircuits.com



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS



REV. OR
YAT-6-D+
6/29/2016
Page 1 of 1