

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	7.00	1.02
0.02	6.99	1.02
0.04	6.99	1.02
0.06	6.99	1.02
0.08	7.00	1.02
0.10	7.00	1.02
0.20	7.00	1.02
0.40	7.00	1.02
0.60	6.99	1.02
0.80	6.99	1.02
1.00	6.99	1.02
1.20	6.99	1.02
1.40	6.99	1.03
1.60	7.00	1.03
1.80	6.99	1.03
2.00	6.99	1.04
3.00	7.00	1.05
4.00	7.00	1.07
5.00	7.01	1.09
6.00	6.97	1.11
7.00	7.01	1.12
8.00	7.03	1.14
9.00	7.05	1.15
10.0	7.07	1.17
11.0	7.10	1.18
12.0	7.12	1.20
13.0	7.09	1.22
14.0	7.19	1.24
15.0	7.10	1.27
16.0	7.14	1.28
17.0	7.24	1.29
18.0	7.26	1.30
19.0	7.27	1.32
20.0	7.29	1.35
21.0	7.34	1.36
22.0	7.33	1.38
23.0	7.47	1.40
24.0	7.43	1.41
25.0	7.42	1.43
26.0	7.49	1.44
27.0	7.53	1.46
28.0	7.77	1.47
29.0	7.70	1.48
30.0	7.52	1.50
31.0	7.64	1.50
32.0	8.07	1.51
33.0	7.76	1.51
34.0	7.79	1.53
35.0	7.95	1.54
36.0	8.13	1.54
37.0	8.11	1.56
38.0	7.94	1.57
39.0	8.20	1.59
40.0	8.82	1.62