

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	9.01	1.07
0.02	9.00	1.07
0.04	9.00	1.07
0.06	9.00	1.07
0.08	9.00	1.07
0.10	9.00	1.07
0.20	9.01	1.07
0.40	9.01	1.07
0.60	9.01	1.07
0.80	9.01	1.07
1.00	9.01	1.07
1.20	9.00	1.08
1.40	9.01	1.08
1.60	9.00	1.08
1.80	9.01	1.08
2.00	9.01	1.08
3.00	9.00	1.08
4.00	9.00	1.09
5.00	9.00	1.10
6.00	9.02	1.11
7.00	9.02	1.13
8.00	9.04	1.14
9.00	9.04	1.15
10.0	9.06	1.16
11.0	9.07	1.18
12.0	9.09	1.19
13.0	9.17	1.20
14.0	9.10	1.22
15.0	9.12	1.24
16.0	9.14	1.25
17.0	9.16	1.25
18.0	9.21	1.26
19.0	9.31	1.30
20.0	9.35	1.34
21.0	9.46	1.33
22.0	9.42	1.30
23.0	9.37	1.31
24.0	9.54	1.36
25.0	9.47	1.39
26.0	9.50	1.39
27.0	9.53	1.39
28.0	9.68	1.42
29.0	9.67	1.44
30.0	9.64	1.44
31.0	9.64	1.44
32.0	9.67	1.46
33.0	9.72	1.49
34.0	9.82	1.47
35.0	9.88	1.47
36.0	9.91	1.47
37.0	10.14	1.48
38.0	10.03	1.50
39.0	10.10	1.52
40.0	10.65	1.55