

16 Way-0° Power Splitter/Combiner

ZFSC-16-1+

Typical Performance Data

FREQ. (MHz)	TOTAL LOSS ¹ (dB)	AMP. UNBAL. (dB)	ISOLATION (dB)		FREQ. (MHz)	VSWR (:1)	
			Adjacent	Opposite		S	OUTPUTS
0.5	12.66	0.01	44.58	29.35	0.5	1.28	1.27
2.1	12.52	0.01	52.00	31.48	2.1	1.19	1.15
4.9	12.41	0.00	47.05	32.63	4.9	1.22	1.11
8.3	12.43	0.00	42.86	32.96	8.3	1.22	1.11
16.1	12.50	0.00	37.73	32.85	16.1	1.24	1.10
23.8	12.54	0.02	34.63	32.36	23.8	1.28	1.10
31.6	12.57	0.02	32.54	31.81	31.6	1.31	1.10
47.2	12.65	0.01	29.72	30.60	47.2	1.37	1.10
55.0	12.75	0.00	28.80	30.08	55.0	1.39	1.10
62.8	12.74	0.01	28.00	29.52	62.8	1.41	1.09
78.3	12.80	0.01	26.92	28.64	78.3	1.43	1.09
90.1	12.85	0.00	26.45	28.13	90.1	1.43	1.09
100.1	12.85	0.01	26.21	27.75	100.1	1.41	1.08
113.5	12.88	0.00	26.21	27.45	113.5	1.37	1.07
125.0	12.84	0.01	26.39	27.22	125.0	1.32	1.07

¹ Total Loss = Insertion Loss+ 12dB Splitter Loss



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 334-4500 Fax (718) 333-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

RF/MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuits' applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"). Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

REV. OR
ZFSC-16-1+
100627
Page 1 of 1