



## THIRD ANGLE PROJECTION



## REVISIONS


| REV OR | ECN No. | DESCRIPTION | DATE     | DR | AUTH |
|--------|---------|-------------|----------|----|------|
|        | M113234 | NEW RELEASE | 09/04/07 | AV | DJ   |
|        |         |             |          |    |      |
|        |         |             |          |    |      |
|        |         |             |          |    |      |

### SUGGESTED MOUNTING CONFIGURATION FOR TTT1289 CASE STYLE, "su" PIN CONNECTION



- NOTE: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS  $.030'' \pm .002''$ ; COPPER: 1/2 OZ. EACH SIDE.  
FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

 DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER).

 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED

INITIALS

DATE

DIMENSIONS ARE IN INCHES

TOLERANCES ON:

2 PL DECIMALS  $\pm$ 3 PL DECIMALS  $\pm$  .005ANGLES  $\pm$ FRACTIONS  $\pm$ 

DRAWN

AV

08/28/07

CHECKED

MMG

09/04/07

APPROVED

DJ

09/04/07



**Mini-Circuits®** 13 Neptune Avenue  
Brooklyn NY 11235

PL, su, TTT1289, SYIQ-895M+, TB-459+

 Mini-Circuits®

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.

SIZE

A

CODE IDENT

15542

DRAWING NO:

98-PL-280

REV:

OR

FILE:

98PL280

SCALE:

5:1

SHEET:

1 OF 1

ASHEETA1.DWG REV:A DATE:01/12/95