



REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	NPO-005684	NEW RELEASE	OCT 25	SS	VR

1. TRACE WIDTH ARE SHOWN FOR ROGERS (RO4350B) WITH DIELECTRIC THICKNESS .010"±.001"
COPPER: 1/2 Oz EACH SIDE. FOR OTHER MATERIAL TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

DENOTES PCB COPPER LAYOUT WITH SMOBC
(SOLDER MASK OVER BARE COPPER)



DENOTES COPPER LAND PATTERN FREE OF SOLDERMASK

UNLESS OTHERWISE SPECIFIED

INITIALS

DATE _____

DIMENSIONS ARE IN INCHES

DRAWN

SS

07 OCT 25

TOLERANCES ON:

CHECKED

MD

16 OCT 25

3 PL DECIMALS $\pm .005"$

APPROVED

NK

16 OCT 25

ANGLES $\pm$
FRACTIONS $\pm$

 Mini-Circuits®

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE , MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.



Mini-Circuits®

13 Neptune Avenue
Brooklyn NY 11235

PL, BBE3695, TB-1318, 50 0hm

SIZE
A

CODE IDENT
15542

DRAWING NO:
98-PL-840

REV: OR

FILE: 98-PL-840

SCALE: 2.4:1

SHEET:	1	OF	1
--------	---	----	---

ASHEETA1.DWG REV:A DATE:01/12/95