SMA Fixed Attenuator

15dB

FW-15+

50Ω **1W Maximum Ratings**

Operating Temperature -45°C to 100°C Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded

Features

- wideband coverage, DC to 12000 MHz
- 1 watt rating
- rugged unibody construction

DC to 12000 MHz

- · off-the-shelf availability
- very low cost

Applications

- impedance matching
- · signal level adjustment



Generic photo used for illustration purposes only


CASE STYLE: FF704

Connectors	Model		
SMA	FW-15+		

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Outline Drawing



Outline Dimensions (inch)

В D Ε .410 1.43 .312 grams 10 41 36.32 7 92 10.0

Electrical Specifications at 25°C


Parameter	Condition (MHz)	Min.	Тур.	Max.	Unit	
Frequency Range		DC	_	12000	MHz	
	10	_	15	_		
	DC - 3000	14.5	15.15	15.85		
Attenuation	3000 - 8000	14.8	15.65	16.6	dB	
	8000 - 12000	15.45	16.3	17.2		
	DC - 3000	_	1.05	1.20		
VSWR	3000 - 8000	_	1.20	1.35	:1	
	8000 - 12000		1.30			


1. Flatness = variation over band divided by 2.


Typical Performance Data

Frequency (MHz)	Attenuation (dB)	VSWR (:1)
10.00	15.00	1.02
100.00	15.02	1.02
2000.00	15.22	1.03
3000.00	15.33	1.04
6000.00	15.72	1.08
8000.00	16.00	1.19
10000.00	16.21	1.27
11000.00	16.24	1.28
11500.00	16.24	1.28
12000.00	16.22	1.30
15000.00	15.97	1.17

Electrical Schematic







- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Terms"): Purchases of this part. Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp