50Ω

SMA Fixed Attenuator

9dB

Generic photo used for illustration purposes only

CASE STYLE: FF704

Connectors Model SMA FW-9+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Maximum Ratings

Operating Temperature -45°C to 100°C Storage Temperature -55°C to 100°C

1W

Permanent damage may occur if any of these limits are exceeded

Outline Drawing



Outline Dimensions (inch)

В D Ε .410 1.43 .312 grams 10 41 36.32 7 92 10.0

Features

- wideband coverage, DC to 12000 MHz
- 1 watt rating
- rugged unibody construction

DC to 12000 MHz

- · off-the-shelf availability
- very low cost

Applications

- impedance matching
- · signal level adjustment

Electrical Specifications at 25°C


·					
Parameter	Condition (MHz)	Min.	Тур.	Max.	Unit
Frequency Range		DC	_	12000	MHz
Attenuation	10	_	9	_	
	DC - 3000	8.6	9.15	9.7	
	3000 - 8000	8.8	9.45	10.35	dB
	8000 - 12000	9.1	9.85	10.5	
	DC - 3000	_	1.05	1.20	
VSWR	3000 - 8000	_	1.15	1.35	:1
	8000 - 12000	_	1.35	_	
Input Power	DC - 12000	_	_	1.0	W


^{1.} Flatness = variation over band divided by 2.


Typical Performance Data

Frequency (MHz)	Attenuation (dB)	VSWR (:1)
10.00	9.00	1.02
100.00	9.03	1.01
2000.00	9.18	1.02
3000.00	9.26	1.04
6000.00	9.50	1.09
8000.00	9.70	1.19
10000.00	9.84	1.33
11000.00	9.89	1.35
11500.00	9.91	1.35
12000.00	9.91	1.35
15000.00	9.78	1.15

Electrical Schematic







- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Topod"). Durch search of this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Topod"). Durch search of this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Topod"). Durch search of this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Topod"). Durch search of this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Topod"). Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp