

## Frequency Mixer

## HJK-ED11090/1

Level 17 (LO Power + 17 dBm)

### Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE : TTT167

| ELECTRICAL SPECIFICATIONS 50Ω @ +25°C |                                        |      |      |      |       |
|---------------------------------------|----------------------------------------|------|------|------|-------|
| Parameter                             |                                        | Min. | Typ. | Max. | Units |
| Frequency                             | LO (f <sub>L</sub> to f <sub>U</sub> ) | 1040 |      | 1390 | MHz   |
|                                       | RF (f <sub>L</sub> to f <sub>U</sub> ) | 1040 |      | 1390 | MHz   |
|                                       | IF                                     | 10   |      | 500  | MHz   |
| Conversion Loss                       | Total Range                            |      | 8.3  |      | dB    |
| LO-RF Isolation                       |                                        |      | 32   |      | dB    |
| LO-IF Isolation                       |                                        |      | 36   |      | dB    |
| Input IP3                             |                                        |      | +32  |      | dBm   |
| 1 dB Compression                      |                                        |      | +15  |      | dBm   |

| MAXIMUM RATINGS       |                 |
|-----------------------|-----------------|
| Operating Temperature | -20°C to 85°C   |
| Storage Temperature   | -55°C to +100°C |

| PIN CONNECTIONS |       |
|-----------------|-------|
| LO              | 2     |
| RF              | 1     |
| IF              | 3     |
| GROUND          | 4,5,6 |

### Electrical Schematics

