

## Frequency Mixer

## HJK-ED9605/2

Level 21 (LO Power + 21 dBm)

### Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE : TTT167**

ELECTRICAL SPECIFICATIONS 50Ω @ +25°C					
Parameter		Min.	Typ.	Max.	Units
Frequency	LO (fL to fu)	10		2530	MHz
	RF (fL to fu)	10		2530	MHz
	IF	10		480	MHz
Conversion Loss	Mid band		6.4		dB
	Total Range		7.0		dB
LO-RF Isolation	Low Range		46		dB
	Mid Range		44		dB
	Upper Range		44		dB
LO-IF Isolation	Low Range		57		dB
	Mid Range		44		dB
	Upper Range		40		dB
Input IP3			+26		dBm
1 dB Compression			+16		dBm

**Note:** Low Range = [fL to 10fL]  
Mid band = [2fL to fu/2]

Mid Range = [10fL to fu/2]

Upper Range = [fu/2 to fu]

MAXIMUM RATINGS	
Operating Temperature	-20°C to 85°C
Storage Temperature	-55°C to +100°C

PIN CONNECTIONS	
LO	3
RF	1
IF	2
GROUND	4,5,6