

## Engineering Development Model

### Voltage Controlled Oscillator

JTOS-ED6120/3

#### Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability.

At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE : BK377

| ELECTRICAL SPECIFICATIONS 50Ω      |      |          |      |        |
|------------------------------------|------|----------|------|--------|
| Parameter                          | Min. | Typ.     | Max. | Units  |
| Frequency                          | 1886 |          | 2394 | MHz    |
| Tuning Voltage                     | 0.5  |          | 8    | V      |
| Power Output                       |      | +6       |      | dBm    |
| Phase Noise                        |      |          |      |        |
| at 1 kHz offset                    |      | -65      |      | dBc/Hz |
| at 10 KHz offset                   |      | -92      |      | dBc/Hz |
| at 100 KHz offset                  |      | -112     |      | dBc/Hz |
| at 1000 kHz offset                 |      | -132     |      | dBc/Hz |
| Pulling at 12 dBm PK-PK all phases |      | 15       |      | MHz    |
| Pushing at Vcc=5V±0.25V            |      | 5        |      | MHz/V  |
| Tuning Sensitivity                 |      | 70 - 120 |      | MHz/V  |
| Harmonic Suppression               |      | -15      |      | dBc    |
| 3 dB Modulation Bandwidth          |      | 10000    |      | kHz    |
| Supply Voltage                     |      | 5        |      | V      |
| Supply Current                     |      |          | 25   | mA     |

| MAXIMUM RATINGS                 |                |
|---------------------------------|----------------|
| Operating Temperature           | -55°C to 85°C  |
| Storage Temperature             | -55°C to 100°C |
| Absolute Supply Voltage (Vcc)   | +7V            |
| Absolute Tuning Voltage (Vtune) | +10V           |

| PIN CONNECTIONS |                           |
|-----------------|---------------------------|
| RF OUT          | 10                        |
| VCC             | 14                        |
| V-TUNE          | 5                         |
| GROUND          | 1,3,4,6,7,8,9,10,11,12,14 |