

High IP3 Frequency Mixer

LAVI-711H+

Level 17 (LO Power +17 dBm) 220 to 710 MHz

Maximum Ratings

Operating Temperature	-45°C to 85°C
Storage Temperature	-55°C to 100°C
LO Power	+23 dBm
RF Power	+21 dBm

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

LO	10
RF	2
IF	14
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16

Features

- very high IP3, 30 dBm typ.
- low conversion loss, 7.3 dB typ.
- excellent L-R isolation, 50 dB typ. and L-I isolation, 40 dB typ.
- high 1 dB compression, 20 dBm typ.
- shielded metal cover
- aqueous washable
- protected by US Patent 6,807,407

Applications

- cellular/PCS base stations
- ISM applications
- defense communications



Generic photo used for illustration purposes only

CASE STYLE: CK605


+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications (T_{AMB} = 25°C)

FREQUENCY (MHz)			CONVERSION LOSS (dB)			RF in at 1dB Compr (dBm)	IP3 (dBm)	LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)	
RF	LO	IF	Typ.	σ	Max.	Typ.	Typ.	Typ.	Min.	Typ.	Min.
220-710	250-740	10-500	7.3	0.25	9.0	+20	30	50	40	40	29

Outline Drawing




Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K
.500	.500	.180	.100	.080	.115	.060	.040	.540	.060
12.7	12.7	4.572	2.54	2.032	2.921	1.524	1.016	13.72	1.524

L	M	N	P	Q	R	S	T	wt.
.100	.135	.135	.115	.140	.070	.150	.070	grams
2.54	3.429	3.429	2.921	3.556	1.778	3.81	1.778	1.0

Demo Board MCL P/N: TB-433+ Suggested PCB Layout (PL-012)




- NOTES: 1. TRACE WIDTH IS SHOWN FOR FR4 WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
 2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
- DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)	IP3 (dBm)	IF Freq. (MHz)	VSWR IF (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
220.10	250.10	7.37	58.20	42.61	1.24	3.44	27.05	10.10	1.07
245.10	275.10	7.33	58.37	41.84	1.27	3.44	27.24	50.10	1.10
270.10	300.10	7.38	58.15	41.44	1.27	3.40	27.47	100.10	1.18
295.10	325.10	7.39	59.45	40.60	1.28	3.35	27.83	150.10	1.30
320.10	350.10	7.29	57.31	40.07	1.30	3.31	28.59	200.10	1.37
345.10	375.10	7.31	56.89	39.15	1.30	3.22	28.92	250.10	1.49
370.10	400.10	7.33	56.33	38.49	1.31	3.12	28.72	300.10	1.55
395.10	425.10	7.26	55.25	37.32	1.33	2.96	29.29	350.10	1.68
420.10	450.10	7.27	54.20	36.46	1.35	2.78	30.08	360.10	1.66
445.10	475.10	7.28	54.23	35.93	1.34	2.57	30.08	370.10	1.71
470.10	500.10	7.31	53.26	35.82	1.34	2.34	30.88	380.10	1.72
495.10	525.10	7.34	50.69	34.89	1.36	2.11	31.80	390.10	1.69
520.10	550.10	7.57	48.58	32.99	1.35	1.92	32.30	400.10	1.74
545.10	575.10	7.78	48.42	31.25	1.32	1.78	30.64	410.10	1.81
570.10	600.10	7.55	47.58	31.44	1.30	1.75	30.23	420.10	1.79
595.10	625.10	7.40	45.58	32.28	1.31	1.81	30.72	430.10	1.81
620.10	650.10	7.43	43.91	33.02	1.32	1.92	30.51	440.10	1.86
645.10	675.10	7.47	42.94	33.63	1.33	2.06	30.05	450.10	1.86
670.10	700.10	7.49	42.71	34.42	1.34	2.24	29.07	460.10	1.83
710.10	740.10	7.55	43.16	35.55	1.37	2.52	27.02	500.10	1.94








Electrical Schematic



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp





Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp