

## Frequency Mixer

## LOUE-ED3653A/2

Level 10 (LO Power +10 dBm)

### Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE : A01**

ELECTRICAL SPECIFICATIONS 50Ω @ +25°C					
Parameter		Min.	Typ.	Max.	Units
Frequency	LO (fL to fU)	40		2500	MHz
	RF (fL to fU)	40		2500	MHz
	IF	10		900	MHz
Conversion Loss	mid band		6.1		dB
	Total Range		6.1		dB
LO-RF Isolation	Low Range		36		dB
	Mid Range		33		dB
	Upper Range		31		dB
LO-IF Isolation	Low Range		43		dB
	Mid Range		33		dB
	Upper Range		28		dB

**Note:** Low Range = [fL to 10fL]      Mid Range = [10fL to fU/2]      Upper Range = [fU/2 to fU]  
mid band = [2fL to fU/2]

MAXIMUM RATINGS	
Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C

PIN CONNECTIONS	
LO	8
RF	1
IF	3, 4 ^
GROUND	2, 5, 6, 7

^ - pins must be connected together externally