

# Voltage Controlled Oscillator

ROS-780R+

50Ω 720 to 780 MHz

## The Big Deal:

- Low Phase Noise
- High Power Output
- Robust design and construction
- Small size .500" x .500" x .180"



CASE STYLE: CK605

## Product Overview:

The ROS-780R+ is a Voltage Controlled Oscillator, designed to operate from 720 to 780 MHz for mobile radio applications. The ROS-780R+ is packaged in a metal case (size of .500" x .500" x .180") to shield against unwanted signals and noise.

## Key Features

Feature	Advantages
Linear Tuning Sensitivity Ratio: 1.27:1 typ.	Optimal for loop filter design.
Low Phase Noise: -112 dBc/Hz typ at 10kHz offset	Low phase noise improves system EVM (Error Vector Magnitude).
High Power Output, +10 dBm typ.	Reduces amplification requirements and improves immunity to external noise sources.
Good Pushing, 0.7 MHz/V typ.	Provides increased immunity against noisy DC lines and improves output frequency stability vs. variations in supply voltage.
Small size, .500" x .500" x .180"	The small size enables the ROS-780R+ to be used in compact designs.

# Voltage Controlled Oscillator

## ROS-780R+

Linear Tuning 720 to 780 MHz



CASE STYLE: CK605

### Features

- low phase noise, -112 dBc/Hz typ. @ 10kHz offset
- linear tuning characteristics
- high power output, +10 dBm typ.
- low pushing, 0.7 MHz/V typ.
- aqueous washable

### Applications

- wireless communications
- mobile radio services

**+RoHS Compliant**  
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Electrical Specifications

MODEL NO.	FREQ. (MHz)		POWER OUTPUT (dBm)	PHASE NOISE dBc/Hz SSB at offset frequencies, kHz				TUNING					NON HARMONIC SPURIOUS (dBc)		HARMONICS (dBc)		PULLING pk-pk @12 dB (MHz)	PUSHING (MHz/V)	DC OPERATING POWER			
	Min.	Max.		Typ.	1	10	100	1000	VOLTAGE RANGE (V)	SENSITIVITY (MHz/V)	PORT CAP (pF)	3 dB MODULATION BANDWIDTH (MHz)	Typ.	Typ.	Typ.	Max.			Typ.	Max.	Vcc	Current (mA)
	Typ.																					
ROS-780R+	720	780	+10	-87	-112	-133	-154	0.5	12	11 - 14	170	20	-90	-21	-14	1	0.7	12	26			

### Pin Connections

RF OUT	10
VCC	14
V-TUNE	2
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16

### Maximum Ratings

Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Max. Supply Voltage (Vcc)	13V
Absolute Max. Tuning Voltage (Vtune)	14V
All specifications	50 ohm system


Permanent damage may occur if any of these limits are exceeded.

### Tape & Reel: F37


7" Reels with 10, 20, 50, 100 devices  
13" Reels with 200, 500 devices

### Environmental Ratings: ENV65


### Outline Drawing



### PCB Land Pattern



### Demo Board MCL P/N: TB-10 Suggested PCB Layout (PL-012)



### NOTES:







1. TRACE WIDTH IS SHOWN FOR FR4 WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
  2. BOTTOM SIDE OF THE BOTTOM IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)  
 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

### Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt.
.500	.500	.180	.100	.080	.115	.060	.040	.540	.060	.100	.135	.135	.115	.140	.070	.150	.070	grams
12.70	12.70	4.57	2.54	2.03	2.92	1.52	1.02	13.72	1.52	2.54	3.43	3.43	2.92	3.56	1.78	3.81	1.78	1.0

V TUNE	TUNE SENS (MHz/V)	FREQUENCY (MHz)			POWER OUTPUT (dBm)			I <sub>cc</sub> (mA)	HARMONICS (dBc)			FREQ. PUSH (MHz/V)	FREQ. PULL (MHz)	PHASE NOISE (dBc/Hz) at offsets				FREQ OFFSET (kHz)	PHASE NOISE at 750 MHz (dBc/Hz)
		-55°C	+25°C	+85°C	-55°C	+25°C	+85°C		F2	F3	F4			1kHz	10kHz	100kHz	1MHz		
0.00	19.50	677.8	675.0	672.4	9.34	9.09	8.65	20.85	-18.6	-34.5	-32.8	0.55	2.21	-85.76	-112.5	-133.1	-153.0	1.0	-87.67
0.50	15.55	687.2	684.7	682.6	9.63	9.39	8.98	21.03	-18.6	-34.3	-31.2	0.43	1.80	-87.50	-114.3	-135.7	-155.6	2.5	-100.02
1.00	13.91	695.0	692.5	690.4	9.72	9.48	9.07	21.07	-18.6	-33.7	-30.7	0.27	1.59	-89.46	-115.8	-136.9	-156.8	3.6	-103.53
2.00	13.00	708.6	706.1	703.9	9.92	9.68	9.26	21.12	-18.9	-33.1	-30.4	0.17	1.29	-87.52	-117.1	-137.4	-157.5	7.1	-110.48
2.50	13.00	715.2	712.6	710.4	10.02	9.77	9.35	21.14	-19.2	-33.4	-29.8	0.15	1.12	-89.17	-116.8	-137.2	-157.3	8.4	-111.95
3.00	13.12	721.7	719.1	716.9	10.11	9.85	9.44	21.16	-19.4	-33.7	-29.6	0.14	0.93	-89.54	-116.8	-137.3	-157.6	10.0	-113.95
3.50	13.24	728.3	725.6	723.4	10.18	9.93	9.51	21.18	-19.1	-33.5	-30.1	0.16	0.70	-88.42	-116.1	-137.1	-156.9	23.1	-122.23
4.00	13.30	734.9	732.3	730.0	10.25	9.99	9.58	21.20	-19.3	-33.3	-29.8	0.19	0.46	-88.19	-116.0	-136.6	-156.8	38.8	-126.63
4.50	13.31	741.6	738.9	736.7	10.31	10.05	9.65	21.21	-19.8	-33.5	-29.7	0.25	0.47	-89.74	-115.2	-135.9	-156.3	64.0	-130.84
5.00	13.26	748.2	745.6	743.4	10.38	10.11	9.69	21.22	-20.1	-33.0	-29.7	0.32	0.75	-88.33	-115.6	-135.4	-155.9	89.8	-134.00
6.00	12.83	761.2	758.7	756.7	10.47	10.17	9.76	21.25	-20.1	-31.3	-29.4	0.49	1.54	-85.92	-113.2	-134.0	-154.2	100.0	-134.82
6.50	12.54	767.6	765.2	763.2	10.51	10.20	9.79	21.26	-19.8	-31.1	-29.6	0.57	1.90	-85.85	-112.4	-133.3	-154.0	150.8	-138.43
7.00	12.21	773.8	771.4	769.5	10.53	10.22	9.81	21.28	-20.0	-30.2	-28.9	0.65	2.20	-85.46	-111.4	-132.8	-153.2	177.0	-140.10
7.50	11.84	779.8	777.5	775.6	10.55	10.23	9.82	21.28	-20.3	-29.4	-29.1	0.71	2.42	-84.85	-111.4	-132.4	-152.7	211.6	-141.63
8.00	11.44	785.7	783.4	781.6	10.57	10.24	9.82	21.29	-20.6	-29.8	-29.8	0.76	2.56	-86.59	-111.0	-131.9	-152.5	297.1	-144.50
8.50	11.02	791.5	789.2	787.3	10.56	10.23	9.82	21.31	-20.8	-30.5	-29.7	0.80	2.61	-85.75	-110.3	-131.6	-152.3	348.8	-145.51
9.50	10.07	802.3	800.0	798.1	10.51	10.18	9.77	21.33	-21.1	-30.6	-29.5	0.82	2.51	-87.08	-110.0	-131.6	-152.3	489.7	-149.29
10.50	9.01	812.1	809.8	808.0	10.42	10.09	9.68	21.34	-21.3	-30.8	-30.7	0.80	2.23	-83.85	-110.4	-131.8	-152.4	585.4	-150.76
11.50	7.84	820.9	818.5	816.7	10.34	9.99	9.58	21.37	-21.9	-31.0	-30.3	0.76	1.86	-84.08	-111.1	-132.1	-152.7	964.9	-155.05
12.00	7.25	824.8	822.4	820.6	10.30	9.95	9.53	21.38	-21.9	-30.9	-30.7	0.74	1.68	-85.20	-111.2	-132.2	-152.9	1000.0	-155.50

\*at 25°C unless mentioned otherwise



### Additional Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)