

# Engineering Development Model

## Voltage Controlled Oscillator

## ROS-ED14503/1

### Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.

Please click "Back", and then click "Contact Us" for Applications support.



CASE STYLE : CK605

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Typ.	Max.	Units
Frequency	977		1018	MHz
Tuning Voltage	.5		4.5	V
Power Output		0		dBm
Phase Noise				
at 1 kHz offset		-87		dBc/Hz
at 10 KHz offset		-115		dBc/Hz
at 100 KHz offset		-138		dBc/Hz
at 1000 kHz offset		-158		dBc/Hz
Pulling at 12 dB PK-PK all phases		0.25		MHz
Pushing at Vcc ± 5%		0.15		MHz/V
Tuning Sensitivity		18-21		MHz/V
Harmonic Suppression		-18		dBc
3 dB Modulation Bandwidth		110,000		kHz
Supply Voltage		5		V
Supply Current		40		mA

MAXIMUM RATINGS	
Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Supply Voltage (Vcc)	+6V
Absolute Tuning Voltage (Vtune)	+6V

PIN CONNECTIONS	
RF OUT	10
VCC	14
V-TUNE	2
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16