Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR10232/1

CASE STYLE: CK1113

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

		<u> </u>		
ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Тур.	Max.	Units
Frequency	2496		2496	MHz
Tuning Voltage	1		4.0	V
Power Output		+8.5		dBm
Phase Noise				10
at 1 kHz offse	et	-90		dBc/Hz
at 10 KHz offse	et /	-114		dBc/Hz
at 100 KHz offse	et 🦰	-135		dBc/Hz
at 1000 kHz offse	et	-155	4	dBc/Hz
Pulling at 12 dBr PK-PK all phases		1.3		MHz
Pushing at Vcc=6.5V±0.325V		0.015		MHz/V
Tuning Sensitivity	201	9		MHz/V
Harmonic Suppression	2	-23	-16	dBc
3 dB Modulation Bandwidth	4	140000		kHz
Supply Voltage		6.5		V
Supply Current	40		36	mA

MAXIMUM RATINGS		
Operating Temperature	-55°C to 85°C	
Storage Temperature	-55°C to 100°C	
Absolute Supply Voltage (Vcc)	+8.5V	
Absolute Tuning Voltage (Vtune)	+6V	

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	