Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR10332/1

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK605

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	1270		2220	MHz	
Tuning Voltage	1.6		18.5	V	
Power Output		+8		dBm	
Phase Noise					
at 1 kHz offset		-75		dBc/Hz	
at 10 KHz offset		-101		dBc/Hz	
at 100 KHz offset		-123		dBc/Hz	
at 1000 kHz offset		-143		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		1.1		MHz	
Pushing at Vcc=5V±0.25V		0.7		MHz/V	
Tuning Sensitivity		47 - 78		MHz/V	
Harmonic Suppression		-19		dBc	
3 dB Modulation Bandwidth		75000		kHz	
Supply Voltage		5		V	
Supply Current			50	mA	

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+7V		
Absolute Tuning Voltage (Vtune)	+20.5V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

140324