## Engineering Development Model

## **Voltage Controlled Oscillator**

## ROS-EDR10437MP

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE: CK605** 

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Тур.	Max.	Units
Frequency	1600		2000	MHz
Tuning Voltage	0.5		10.0	V
Power Output		+9		dBm
Phase Noise				
at 1 kHz offset		-69		dBc/Hz
at 10 KHz offset		-93		dBc/Hz
at 100 KHz offset		-114		dBc/Hz
at 1000 kHz offset		-134		dBc/Hz
Pulling at 12 dBr PK-PK all phases		17.7		MHz
Pushing at Vcc=5V±0.25V		2.7		MHz/V
Tuning Sensitivity		94 - 119		MHz/V
Harmonic Suppression		-30	-10	dBc
3 dB Modulation Bandwidth		70000		kHz
Supply Voltage		5		V
Supply Current			30	mA

MAXIMUM RATINGS		
Operating Temperature	-55°C to 85°C	
Storage Temperature	-55°C to 100°C	
Absolute Supply Voltage (Vcc)	+7V	
Absolute Tuning Voltage (Vtune)	+12V	

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

Notes
A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

140324

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. Climater and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled to the rights and benefits contained therms. For a full statement of the Standard Terms and the exclusive rights and benefits contained therms. For a full statement of the Standard Terms and the exclusive rights and remodes the sundard, place viait Mini-Circuit's velocity at www.minicro.bis.com/MCLStoreterms.pg