Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR10817

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK605

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Тур.	Max.	Units
Frequency	3500		4500	MHz
Tuning Voltage	1		17.0	V
Power Output		+5		dBm
Phase Noise				
at 1 kHz offset		-64		dBc/Hz
at 10 KHz offset		-89		dBc/Hz
at 100 KHz offset		-112		dBc/Hz
at 1000 kHz offset		-133		dBc/Hz
Pulling at 12 dBr PK-PK all phases		1.3		MHz
Pushing at Vcc=5V±0.25V		3.1		MHz/V
Tuning Sensitivity		80 - 91		MHz/V
Harmonic Suppression		-17		dBc
3 dB Modulation Bandwidth		185000		kHz
Supply Voltage		5		V
Supply Current			50	mA

MAXIMUM RATINGS		
Operating Temperature	-55°C to 85°C	
Storage Temperature	-55°C to 100°C	
Absolute Supply Voltage (Vcc)	+7V	
Absolute Tuning Voltage (Vtune)	+19V	

PIN CONNECTIONS			
RF OUT	10		
VCC	14		
V-TUNE	2		
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16		

Notes
A. Performance and qualify attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled to the eights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and semides thereunder, place with Mini-Circuit's velocity at www.minicruits.com/MCLStore-terms.jp