Engineering Development Model

Voltage Controlled Oscillator

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.

Please click "Back", and then click "Contact Us" for Applications support.

ROS-EDR10979



CASE STYLE: CK1113

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Тур.	Max.	Units
Frequency	5650		5650	MHz
Tuning Voltage	0.5	N K	4.5	V
Power Output		0		dBm
Phase Noise				
at 1 kHz offset		-77		dBc/Hz
at 10 KHz offset		106		dBc/Hz
at 100 KHz offset		-127		dBc/Hz
at 1000 kHz offset		-146		dBc/Hz
Pulling at 12 dBr PK-PK all phases		0.8		MHz
Pushing at Vcc=8V±0.4V		0.3		MHz/V
Tuning Sensitivity	10	26 - 27		MHz/V
Harmonic Suppression		-29	-21	dBc
3 dB Modulation Bandwidth		70000		kHz
Supply Voltage		8		V
Supply Current			25	mA

MAXIMUM RATINGS		
Operating Temperature	-55°C to 85°C	
Storage Temperature	-55°C to 100°C	
Absolute Supply Voltage (Vcc)	+10V	
Absolute Tuning Voltage (Vtune)	+6.5V	

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited versinity and terms and conditions (collectively. "Standard Terms"): Purchasers of this part are entitled to the finite and benefits contained therein. For a full statement of the standard Terms and the exclusive entits and remedies thereunder, please visit Mini-Circuits, com/MCI. Store-terms is